

TRINITY ADVANCED SL TRIATHLON FRAMESET

GIANT



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, L
ΧΡΩΜΑΤΑ	Carbon/Chrome
ΣΚΕΛΕΤΟΣ	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
ΠΙΡΟΥΝΙ	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
ΕΞΑΡΤΗΜΑΤΑ	
TIMONI	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
ΛΑΙΜΟΣ ΣΤΕΛΛΑΣ	Trinity Composite
ARM REST KIT	Sync armrest set

WHEELS	
EXTRAS	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Handlebar Width (mm)	400	400	400
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση