

# TRINITY ADVANCED SL TRIATHLON FRAMESET

**GIANT**



## SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Carbon/Chrome
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STEM	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SEATPOST	Trinity Composite
ARM REST KIT	Sync armrest set

WHEELS	
EXTRAS	Bento box top tube storage, hydration kit, computer mount, 30mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	30mm

**Price: \$6,999.00**

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-685	(TRI) 672-752   (TT) 624-704
Arm Pad Reach	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-430	(TRI) 360-435   (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.