

TRINITY ADVANCED SL TRIATHLON FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Chrome
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STEM	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SEATPOST	Trinity Composite
ARM REST KIT	Sync armrest set

WHEELS	
EXTRAS	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Recommended Retail Price: \$6,000.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (inch)	18.8	20	21.2
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (inch)	20.1	20.9	21.8
Head Tube Length (inch)	3.3	4.1	4.9
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (inch)	1.6	1.6	1.6
Trail (inch)	2.7	2.5	2.5
Wheelbase (inch)	38.3	38.9	39.9
Chain Stay Length (inch)	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.8
Stack (inch)	19.3	20.2	20.9
Reach (inch)	15.6	16.2	17
Stand Over Height (inch)	29.8	30.9	32
Handlebar Width (inch)	15.7	15.7	15.7
Crank Length (inch)	6.3	6.5	6.7
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733 (TT) 605-685 (TRI) 672-752 (TT) 624-70		
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 360-435 (TT) 375-45		
Pad Reach Min (inch)	12.7	13.3	14.1
Pad Reach Max (inch)	15.7	16.3	17

*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.