

TRINITY ADVANCED SL TRIATHLON FRAMESET

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Carbon/Chrome
CUADRO	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
TIJERA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANUBRIO	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
POTENCIA	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
POSTE DE ASIENTO	Trinity Composite
ARM REST KIT	Sync armrest set

RUEDAS	
EXTRAS	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Precio: \$115,000.00

GEOMETRÍA

CUADRO	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	477	508	538
Ángulo de la Base del Poste de Asiento	77.0°	77.0°	77.0°
Longitud del Tubo Superior (mm)	510	530	554
Longitud del Telescopio (mm)	85	105	125
Ángulo del Telescopio	72.0°	73.0°	73.0°
Rake (mm)	40	40	40
Trail (mm)	69	63	63
Distancia entre Ejes (mm)	974	988	1013
Longitud de Vaina Inferior (mm)	405	405	405
Caída del Eje de Centro (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Altura del Tubo Superior al Suelo (mm)	758	786	814
Ancho del Manubrio (mm)	400	400	400
Longitud de la Biela (mm)	160	165	170
Tamaño de las Ruedas	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733 (TT) 605-685 (TRI) 67		
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 36		
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Todas las especificaciones están sujetas a cambios sin previo aviso.