

TRINITY ADVANCED SL TRIATHLON FRAMESET



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Carbon/Chrome
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STUURPEN	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
ZADELPEN	Trinity Composite
ARMSTEUNSET	Sync armrest set

WIELSET	
EXTRA'S	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	30mm

Adviesprijs: € 4.299,00

GEOMETRIE

FRAME	S	M	L
Zitbuis Lengte (mm)	508	538	565
Zitbuis Hoek	77,0°	77,0°	77,0°
Frame Lengte (horizontaal) (mm)	530	554	579
Balhoofdbuis Lengte (mm)	105	125	145
Balhoofdbuis Hoek	73,0°	73,0°	73,0°
Vork Sprong (mm)	40	40	40
Naloop (mm)	63	63	63
Wielbasis (mm)	988	1013	1039
Liggende achtersvork lengte (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stand Over Height (mm)	786	814	838
Stuur breedte (mm)	400	400	400
Cranklengte (mm)	165	170	172,5
Wielmaat	700C	700C	700C
Arm Pad Stack	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704	(TRI) 691-771 (TT) 6
Arm Pad Reach	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450	(TRI) 380-455 (TT) 3
Pad Reach Min (mm)	338	358	378
Pad Reach Max (mm)	413	433	453

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.