

TRINITY ADVANCED SL TRIATHLON FRAMESET

GIANT



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Carbon/Chrome
CADRU	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTE	
GHIDON	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
PIPA	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
TIJA SA	Trinity Composite
ARM REST KIT	Sync armrest set

ROTI	
EXTRAS	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIE

CADRU	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Handlebar Width (mm)	400	400	400
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Toate specificatiile enumerate se pot schimba fara notificare prealabila.