

TRINITY ADVANCED SL TRIATHLON FRAMESET

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Carbon/Chrome
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
OPORA KRMILA	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
OPORA SEDEŽA	Trinity Composite
ARM REST KIT	Sync armrest set

OBROČNIKI	
DODATKI	TT storage, hydration kit, computer mount, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XS	S	M
Dolžina sedežne cevi (mm)	477	508	538
Kot sedežne cevi	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Višina glave okvirja (mm)	85	105	125
Krmilni kot	72,0°	73,0°	73,0°
Zamik vpetja osi (mm)	40	40	40
Trail (mm)	69	63	63
Medosna razdalja (mm)	974	988	1013
Dolžina cevi ob verigi (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	490	513	532
Doseg (mm)	397	412	432
Višina zgornje cevi (mm)	758	786	814
Širina krmila (mm)	400	400	400
Dolžina gonilke (mm)	160	165	170
Velikost obročnikov	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 625-707
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Vse navedene specifikacije se lahko spremenijo brez obvestila.