

TRINITY ADVANCED SL TRIATHLON FRAMESET

GIANT



產品規格

車架	
尺寸	XS, S, M
顏色	Carbon/Chrome
車架	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
前叉	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc

COMPONENTS

車把手	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
把手帶/套	Stratus Lite 2.0
豎桿	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
座桿	Trinity Composite
ARM REST KIT	Sync armrest set

輪組

其他 TT storage, hydration kit, computer mount, 30mm max tire size

LIMITS

MAX TIRE CLEARANCE 30mm

Price: NT\$150,000

車架幾何

車架	XS	S	M	L
座(立)管長 (mm)	477	508	538	565
座(立)管角度	77.0°	77.0°	77.0°	77.0°
上管長度 (mm)	510	530	554	579
頭管長度 (mm)	85	105	125	145
頭管角度	72.0°	73.0°	73.0°	73.0°
前叉 (mm)	40	40	40	40
Trail (mm)	69	63	63	63
前後輪距 (mm)	974	988	1013	1035
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	70	70	70	70
頭碗至五通高度 (mm)	490	513	532	551
頭碗至五通長度 (mm)	397	412	432	452
上管至地面高度 (mm)	758	786	814	838
把手寬 (mm)	400	400	400	400
曲柄長度 (mm)	160	165	170	172
輪組尺寸	700C	700C	700C	700C
肘靠上移範圍	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704	(TRI)
肘靠前伸範圍	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450	(TRI)
Pad Reach Min (mm)	323	338	358	378
Pad Reach Max (mm)	398	413	433	453

*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。