

리볼트 X 어드밴스 PRO 0



스펙

프레임	
사이즈	XS, S, M, M/L
색상	Kelp Forest/Charcoal/Chrome
프레임	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
포크	Fox 32 Float AX Performance Elite, 40mm, Fit 4 damper12x100mm thru-axle
서스펜션	N/A
부품	
핸들바	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm
GRIPS	Stratus Lite 3.0
스텝	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm
싯포스트	Post Moderne, dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
안장	Giant Approach SL
페달	N/A
구동계	
변속기	SRAM Force eTap AXS, 1x12
앞 변속기	N/A
뒷 변속기	SRAM X01 Eagle AXS
브레이크	SRAM Force eTap AXS hydraulic, SRAM CenterLine rotors [F]160mm, [R]160mm
브레이크 레버	SRAM Force eTap AXS hydraulic
스프라켓	SRAM XG-1295, 12-speed, 10x52
체인	SRAM X01 Eagle
크랭크 셋	SRAM Force D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm
BB	SRAM DUB, press fit

바퀴	
휠	Giant CXR 1 X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm
허브	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
스포크	Sapim Laser
타이어	Maxxis Rambler, 700x50c, tubeless
추가 기능	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

가격: ₩8,390,000

지오메트리

프레임	XS	S	M	ML
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
시트 튜브 길이 (mm)	430	450	470	490
시트 튜브 각도	74.0° 73.9°	73.5° 73.4°	73.5° 73.4°	73.0° 72.9°
탐튜브 길이 (mm)	543	553	560	575
헤드 튜브 길이 (mm)	90	100	115	130
헤드튜브 각도	70.5° 70.4°	71.0° 70.9°	71.5° 71.4°	72.0° 71.9°
포크 레이크 (mm)	50	50	50	50
트레일 (mm)	80.3 83.7	76.9 80.3	73.5 76.8	70.1 73.4
휠베이스 (mm)	1023 1033	1024 1034	1026 1036	1031 1041
체인스테이 길이 (mm)	425 435	425 435	425 435	425 435
BB (mm)	68 69	68 69	68 69	68 69
스택 (mm)	549	560	576	592
범위 (mm)	386	387	389	393
스탠드 오버 (mm)	720 726	736 743	755 761	772 778
핸들바 폭 (mm)	440	440	460	460
스텝 길이 (mm)	50	60	70	80
크랭크 길이 (mm)	170	170	172.5	172.5
휠사이즈	700x 42C	700x 42C	700x 42C	700x 42C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.