

XTC ADVANCED 29 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Abyss Black/Steampunk
FRAME	Advanced-grade composite, 12x148mm thru-axle
FORK	Fox 32 Float Step Cast Performance, 100mm, GRIP damper, 44mm offset, two-position remote lockout, Boost 15x110 Kabolt
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XC 35, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STEM	Giant Contact SL XC 35 S:60mm, M:70mm, L:80mm, XL:90mm
SEATPOST	Giant Contact Switch Core dropper, remote S: 100mm travel / 30.9 x 350mm M: 100mm travel / 30.9 x 350mm L: 120mm travel / 30.9 x 400mm XL
SADDLE	Giant Grit SL
DRIVETRAIN	
SHIFTERS	Shimano Deore XT M8100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore XT M8100
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano Deore XT M8120, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant XCR 2 Carbon 29 WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Rekon Race, 29x2.4, [R] Maxxis Rekon Race, 29x2.25, foldable, TLR, EXO
EXTRAS	tubeless prepared, 2.25" max tire size, 38t max chainring size

Recommended Retail Price: \$4,000.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (inch)	15	17	18.7	20.7
Seat Post Insertion Depth (inch)	6.5	8.7	10.2	12.2
Seat Tube Angle	73.5°	73.5°	73.5°	73.5°
Top Tube Length (inch)	23.4	24.2	25	26.2
Head Tube Length (inch)	3.7	3.7	4.1	4.5
Head Tube Angle	69.5°	69.5°	70.0°	70.0°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	3.7	3.7	3.7	3.7
Wheelbase (inch)	42.8	43.5	44.4	45.6
Chain Stay Length (inch)	16.7	16.7	16.7	16.7
Bottom Bracket Drop (inch)	2.3	2.3	2.3	2.3
Stack (inch)	23.8	23.8	24.1	24.9
Reach (inch)	16.4	17.1	17.8	18.8
Stand Over Height (inch)	29	30.1	31.1	32.6
Handlebar Width (inch)	29.9	29.9	29.9	29.9
Stem Length (inch)	2.4	2.8	3.1	3.5
Crank Length (inch)	6.7	6.9	6.9	6.9

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*