

XTC ADVANCED 29 1



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Shoreline/Carbon
CUADRO	Advanced-grade composite, 12x148mm thru-axle
TIJERA	Fox 32 Float SC Performance, 100mm, GRIP damper, 44mm offset, two-position remote lockout, Boost 15x110 Kabolt
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact XC 35, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
POTENCIA	Giant Contact SL XC 35 S:60mm, M:70mm, L:80mm, XL:90mm
POSTE DE ASIENTO	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 125mm
ASIENTO	Fi'zi:k Antares R7 with S-alloy rails
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore XT M8100, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano Deore XT M8100
FRENOS	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100
CASSETTE	Shimano SLX M7100, 10x51
CADENA	KMC X-12
MULTIPLICACIÓN	Shimano Deore XT M8120, 32t S:170mm, M:175mm, L:175mm, XL:175mm
EJE DE CENTRO	Shimano, press fit

RUEDAS	
RUEDAS	Giant XCR 2 Carbon 29 WheelSystem
MAZAS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYOS	Sapim
NEUMÁTICOS	Maxxis Recon Race 29x2.25, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.25" max tire size, 38t max chainring size

Precio: \$92,990.00

GEOMETRÍA

CUADRO	S	M	L
Longitud de la Base del Poste de Asiento (mm)	380	431	475
Seat Post Insertion Depth (mm)	165	220	260
Ángulo de la Base del Poste de Asiento	73.5°	73.5°	73.5°
Longitud del Tubo Superior (mm)	595	614	635
Longitud del Telescopio (mm)	95	95	105
Ángulo del Telescopio	69.5°	69.5°	70.0°
Rake (mm)	43	43	43
Trail (mm)	94.9	94.9	94.9
Distancia entre Ejes (mm)	1087	1106	1128
Longitud de Vaina Inferior (mm)	425	425	425
Caída del Eje de Centro (mm)	58	58	58
Stack (mm)	604	604	613
Reach (mm)	416	435	453
Altura del Tubo Superior al Suelo (mm)	737	764	791
Ancho del Manubrio (mm)	760	760	760
Longitud de la Potencia (mm)	60	70	80
Longitud de la Biela (mm)	170	175	175
Tamaño de las Ruedas	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.