

XTC ADVANCED 29 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Abyss Black/Steampunk
FRAME	Advanced-grade composite, 12x148mm thru-axle
FORK	Fox 32 Float Step Cast Performance, 100mm, GRIP damper, 44mm offset, two-position remote lockout, Boost 15x110 Kabolt
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XC 35, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STEM	Giant Contact SL XC 35 S:60mm, M:70mm, L:80mm, XL:90mm
SEATPOST	Giant Contact Switch Core dropper, remote S: 100mm travel / 30.9 x 350mm M: 100mm travel / 30.9 x 350mm L: 120mm travel / 30.9 x 400mm XL
SADDLE	Giant Grit SL
DRIVETRAIN	
SHIFTERS	Shimano Deore XT M8100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore XT M8100
BRAKES	Shimano Deore XT BR-M8100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano Deore XT M8120, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant XCR 2 Carbon 29 WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Rekon Race, 29x2.4, [R] Maxxis Rekon Race, 29x2.25, foldable, TLR, EXO
EXTRAS	tubeless prepared, 2.25" max tire size, 38t max chainring size

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	380	431	475	525
Seat Post Insertion Depth (mm)	165	220	260	310
Seat Tube Angle	73,5°	73,5°	73,5°	73,5°
Top Tube Length (mm)	595	614	635	665
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	69,5°	69,5°	70,0°	70,0°
Fork Rake (mm)	43	43	43	43
Trail (mm)	95	95	95	95
Wheelbase (mm)	1087	1106	1128	1159
Chain Stay Length (mm)	425	425	425	425
Bottom Bracket Drop (mm)	58	58	58	58
Stack (mm)	604	604	613	632
Reach (mm)	416	435	453	477
Stand Over Height (mm)	737	764	791	829
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	175	175	175

All specifications listed are subject to change without notice.