

XTC ADVANCED 29 1

GIANT



SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	Abyss Black/Steampunk
RAMME	Advanced-grade composite, 12x148mm thru-axle
GAFFEL	Fox 32 Float Step Cast Performance, 100mm, GRIP damper, 44mm offset, two-position remote lockout, Boost 15x110 Kabolt
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact XC 35, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STYRSTEM	Giant Contact SL XC 35 S:60mm, M:70mm, L:80mm, XL:90mm
SETEPINNE	Giant Contact Switch Core dropper, remote S: 100mm travel / 30.9 x 350mm M: 100mm travel / 30.9 x 350mm L: 120mm travel / 30.9 x 400mm XL
SADEL	Giant Grit SL
DRIVVERK	
GIRHENDLER	Shimano Deore XT M8100, 1x12
FRONTGIR	N/A
BAKGIR	Shimano Deore XT M8100
BREMSER	Shimano Deore XT BR-M8100, hydraulic, Giant TR55 rotors [F]180mm, [R]160mm
BREMSEHENDLER	Shimano Deore XT BL-M8100
KASSETT	Shimano SLX M7100, 10x51
KJEDE	KMC X-12
KRANK	Shimano Deore XT M8120, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant XCR 2 Carbon 29 WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EIKE	Sapim
DEKK	[F] Maxxis Rekon Race, 29x2.4, [R] Maxxis Rekon Race, 29x2.25, foldable, TLR, EXO
EXTRAS	tubeless prepared, 2.25" max tire size, 38t max chainring size

GEOMETRI

RAMME	S	M	L	XL
Seat Tube Length (mm)	380	431	475	525
Seat Post Insertion Depth (mm)	165	220	260	310
Seat Tube Angle	73,5°	73,5°	73,5°	73,5°
Top Tube Length (mm)	595	614	635	665
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	69,5°	69,5°	70,0°	70,0°
Fork Rake (mm)	43	43	43	43
Trail (mm)	95	95	95	95
Wheelbase (mm)	1087	1106	1128	1159
Chain Stay Length (mm)	425	425	425	425
Bottom Bracket Drop (mm)	58	58	58	58
Stack (mm)	604	604	613	632
Reach (mm)	416	435	453	477
Stand Over Height (mm)	737	764	791	829
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	175	175	175

Alle spesifikasjonene kan endres uten varsel.