

XTC ADVANCED 29 3

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Black / Sapphire
TELAIO	Advanced-Grade Composite, 12x148mm thru-axle
FORCELLA	Giant Crest 34 RRL, 100mm, remote lockout
AMMORTIZZATORE	N/A
COMPONENTISTICA	
MANUBRIO	Giant Contact SL XC Flat, 780x31.8mm
MANOPOLE	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
ATTACCO MANUBRIO	Giant Contact S:60mm, M:70mm, L:80mm, XL:90mm
REGGISELLA	Giant Connect, 30.9x400mm
SELLA	Giant Approach
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano Deore
FRENI	Shimano BR-MT410, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
COMANDI FRENO	Shimano MT-401
PACCO PIGNONI	Shimano Deore, 11x51
CATENA	KMC X-12
GUARNITURA	Praxis Cadet M24, Boost, 32t
MOVIMENTO CENTRALE	Praxis, press fit

RUOTE	
CERCHI	Giant XCT 29" alloy, 25mm inner width
MOZZI	alloy, sealed bearing
RAGGI	Sapim
COPERTONI	Maxxis Recon Race 29x2.25, foldable, TLR, EXO, tubeless
EXTRA	tubeless prepared, 2.25" max tire size, 38t max chainring size

Prezzo: 2.249,00 €

GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza Tubo Sella (mm)	380	431	475	525
Angolo Tubo Sella	73,5°	73,5°	73,5°	73,5°
Lunghezza Tubo Orizzontale (mm)	595	614	635	665
Lunghezza Tubo Sterzo (mm)	95	95	105	115
Angolo Sterzo	69,5°	69,5°	70,0°	70,0°
Rake Forcella (mm)	43	43	43	43
Avancorsa (mm)	94,9	94,9	94,9	94,9
Interasse (mm)	1087	1106	1128	1159
Lunghezza Carro Posteriore (mm)	425	425	425	425
Drop Movimento Centrale (mm)	58	58	58	58
Stack (mm)	604	604	613	632
Reach (mm)	416	435	453	477
Altezza stand over (mm)	737	764	791	829
Larghezza Manubrio c/c (mm)	760	760	760	760
Lunghezza Attacco Manubrio (mm)	60	70	80	90
Lunghezza Pedivella (mm)	170	175	175	175
Dimensione Ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.