

# XTC SLR 29 1



## SPECIFIKACIJE

| OKVIR               |                                                                      |
|---------------------|----------------------------------------------------------------------|
| VELIKOSTI           | S, M, L, XL                                                          |
| BARVE               | Sea Sparkle, Snow Drift                                              |
| OKVIR               | ALUXX SLR-grade Aluminum                                             |
| VILICE              | Giant Crest 34 RRL, 100mm, 15x110, remote lockout                    |
| AMORTIZER           | N/A                                                                  |
| KOMPONENTE          |                                                                      |
| KRMILO              | Giant Connect XC, 740x31.8mm                                         |
| GRIPS               | Giant Sole-O                                                         |
| OPORA KRMILA        | Giant Contact S:60mm, M:70mm, L:80mm, XL:90mm                        |
| OPORA SEDEŽA        | Giant Connect, 30.9mm S:375mm, M:375mm, L:400mm, XL:400              |
| SEDEŽ               | Giant Sport                                                          |
| PEDALA              | N/A                                                                  |
| POGON               |                                                                      |
| PRESTAVNE ROČICE    | Shimano SLX M-7100, 1x12                                             |
| PREDNJI MENJALNIK   | N/A                                                                  |
| ZADNJI MENJALNIK    | Shimano Deore XT M-8100                                              |
| ZAVORE              | Shimano BR-MT500, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm |
| ZAVORNE ROČICE      | Shimano BR-MT501                                                     |
| VERIŽNIK            | Shimano SLX, 10x51                                                   |
| VERIGA              | KMC X-12                                                             |
| GONILKE Z VERIŽNIKI | Shimano SLX, 32t S:170mm, M:175mm, L:175mm, XL:175mm                 |
| BOTTOM BRACKET      | Shimano, press fit                                                   |

| OBROČNIKI |                                                               |
|-----------|---------------------------------------------------------------|
| OBROČI    | Giant XCT 29, 25mm inner width                                |
| PESTA     | Shimano C500, sealed                                          |
| NAPERE    | stainless                                                     |
| PLAŠČI    | Maxxis Recon Race 29x2.25, foldable, TLR, EXO, tubeless       |
| DODATKI   | tubeless prepared, 2.4" max tire size, 36t max chainring size |

## GEOMETRIJA

| OKVIR                                        | S           | M           | L           | XL          |
|----------------------------------------------|-------------|-------------|-------------|-------------|
| Dolžina sedežne cevi (mm)                    | 380         | 431         | 475         | 525         |
| Seat Post Insertion Depth (mm)               | 335         | 205         | 250         | 300         |
| Kot sedežne cevi                             | 74,0°       | 74,0°       | 74,0°       | 74,0°       |
| Top Tube Length (mm)                         | 595         | 614         | 635         | 665         |
| Višina glave okvirja (mm)                    | 95          | 95          | 105         | 115         |
| Krmilni kot                                  | 69,5°       | 69,5°       | 70,0°       | 70,0°       |
| Zamik vpetja osi (mm)                        | 51          | 51          | 51          | 51          |
| Trail (mm)                                   | 94,9        | 94,9        | 94,9        | 94,9        |
| Medosna razdalja (mm)                        | 1117        | 1136        | 1152        | 1183        |
| Dolžina cevi ob verigi (mm)                  | 440         | 440         | 440         | 440         |
| Bottom Bracket Drop (mm)                     | 58          | 58          | 58          | 58          |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 607         | 607         | 618         | 628         |
| Doseg (mm)                                   | 421         | 440         | 458         | 485         |
| Višina zgornje cevi (mm)                     | 727         | 757         | 785         | 818         |
| Širina krmila (mm)                           | 740         | 740         | 740         | 740         |
| Dolžina opore krmila (mm)                    | 60          | 70          | 80          | 90          |
| Dolžina gonilke (mm)                         | 170         | 175         | 175         | 175         |
| Velikost obročnikov                          | [F] 29" [R] | [F] 29" [R] | [F] 29" [R] | [F] 29" [R] |

Vse navedene specifikacije se lahko spremenijo brez obvestila.