

XTC SLR 29 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Knight Shield, Panther
FRAME	ALUXX SLR-grade Aluminum, 12x148mm thru-axle
FORK	Giant Crest 34 RRL, 100mm, 15x110, remote lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC, 740x31.8mm
GRIPS	Giant Sole-O
STEM	Giant Contact S:60mm, M:70mm, L:80mm, XL:90mm
SEATPOST	Giant Connect, 30.9mm S:375mm, M:375mm, L:400mm, XL:400
SADDLE	Giant Sport
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore M-6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore M-6100
BRAKES	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano BR-MT201
CASSETTE	Shimano Deore, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet, 30t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant XCT 29, 25mm inner width
HUBS	Shimano C500, sealed
SPOKES	stainless
TIRES	Maxxis Recon Race 29x2.25, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 36t max chainring size

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	380	431	475	525
Seat Post Insertion Depth (mm)	335	205	250	300
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	595	614	635	665
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	69,5°	69,5°	70,0°	70,0°
Fork Rake (mm)	51	51	51	51
Trail (mm)	94,9	94,9	94,9	94,9
Wheelbase (mm)	1117	1136	1152	1183
Chain Stay Length (mm)	440	440	440	440
Bottom Bracket Drop (mm)	58	58	58	58
Stack (mm)	607	607	618	628
Reach (mm)	421	440	458	485
Stand Over Height (mm)	727	757	785	818
Handlebar Width (mm)	740	740	740	740
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	175	175	175
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

All specifications listed are subject to change without notice.