

XTC SLR 29 2





SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Mineral Yellow
QUADRO	ALUXX SLR-grade Aluminum, 12x148mm thru-axle
FORQUILHA	Giant Crest 34 RRL, 100mm, 15x110, remote lockout
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Giant Connect XC, 740x31.8mm
PUNHOS	Giant Sole-O
AVANÇO	Giant Contact S:60mm, M:70mm, L:80mm, XL:90mm
ESPIGÃO DE SELIM	Giant Connect, 30.9mm S:375mm, M:375mm, L:400mm, XL:400
SELIM	Giant ErgoContact Trail
PEDAIS	N/A
TRANSMISSÃO	
MANETES	Shimano Deore M-6100, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	Shimano Deore M-6100
TRAVÕES	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Shimano BR-MT201
CASSETTE	Shimano Deore, 10x51
CORRENTE	KMC X-12
CONJUNTO PEDALEIRO	Praxis Cadet, 30t S:170mm, M:175mm, L:175mm, XL:175mm
MOVIMENTO CENTRAL	Praxis, press fit

RODAS	
AROS	Giant XCT 29, 25mm inner width
CUBOS	Shimano C500, sealed
RAIOS	stainless
PNEUS	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 36t max chainring size

Preço: 1 049,00 €

GEOMETRIA

QUADRO	S	M	L	XL
Comprimento do tubo do assento (mm)	380	431	475	525
Seat Post Insertion Depth (mm)	335	205	250	300
Ângulo do tubo do assento	74,0°	74,0°	74,0°	74,0°
Comprimento do tubo superior (mm)	595	614	635	665
Comprimento do tubo principal (mm)	95	95	105	115
Ângulo do tubo principal	69,5°	69,5°	70,0°	70,0°
Garfo ancinho (mm)	51	51	51	51
Trilha (mm)	95	95	95	95
distância entre eixos (mm)	1117	1136	1152	1183
Comprimento Chain Stay (mm)	440	440	440	440
Suporte inferior (mm)	58	58	58	58
Pilha (mm)	607	607	618	628
Alcançar (mm)	421	440	458	485
Altura do standover (mm)	727	757	785	818
Largura do guidão (mm)	740	740	740	740
Comprimento da haste (mm)	60	70	80	90
Comprimento da Manivela (mm)	170	175	175	175

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.