



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Knight Shield, Phantom Green
OKVIR	ALUXX SL-Grade Aluminum with horizontal dropouts, 12x197
VILICE	rigid composite with alloy steerer, 15x150, with low rider rack mounts
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect Trail, 780x31.8mm
GRIPS	Giant Tactal Single
OPORA KRMILA	Giant Contact S:50mm, M:50mm, L:60mm, XL:60mm
OPORA SEDEŽA	Giant Connect, 30.9mm S:375mm, M:375mm, L:400mm, XL:400
SEDEŽ	Giant Sport Comfort
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore
ZAVORE	SRAM Level, hydraulic [F]180mm, [R]160mm rotors
ZAVORNE ROČICE	SRAM Level
VERIŽNIK	Shimano Deore M6100, 10x51
VERIGA	Shimano
GONILKE Z VERIŽNIKI	ProWheel MPX, 28t S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	ProWheel, press fit

OBROČNIKI	
OBROČI	Giant FBR alloy, 27.5", 85mm
PESTA	[F] Giant 15x150 sealed bearing [R] Giant 12x197 sealed bearing
NAPERE	stainless, 14g
PLAŠČI	Maxxis Colossus 27.5x4.5, foldable, TR

GEOMETRIJA

OKVIR	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Dolžina sedežne cevi (mm)	381	432	483	533
Kot sedežne cevi	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	585	605	625	645
Višina glave okvirja (mm)	100	115	130	150
Krmilni kot	68,5°	68,5°	68,5°	68,5°
Zamik vpetja osi (mm)	60	60	60	60
Trail (mm)	90,1	90,1	90,1	90,1
Medosna razdalja (mm)	1128,6	1149,8	1171,1	1192,7
Dolžina cevi ob verigi (mm)	445 460	445 460	445 460	445 460
Bottom Bracket Drop (mm)	75	75	75	75
Oddaljenost zgornje cevi od gonilne osi (mm)	621,5	635,5	649,4	668
Doseg (mm)	395	410,7	426,5	440,8
Višina zgornje cevi (mm)	719	735	772	811
Širina krmila (mm)	780	780	780	780
Dolžina opore krmila (mm)	50	50	60	70
Dolžina gonilke (mm)	170	170	175	175
Velikost obročnikov	27.5	27.5	27.5	27.5

Vse navedene specifikacije se lahko spremenijo brez obvestila.