



## СПЕЦИФИКАЦИИ

ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ	
<b>МОТОР</b>	SyncDrive Pro2, 85Nm, powered by Yamaha
<b>КОНТРОЛЕР</b>	RideControl Ergo, 5 power levels plus Smart Assist auto mode
<b>ДИСПЛЕЙ</b>	N/A
<b>БАТЕРИЯ</b>	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
<b>ЗАРЯДНО</b>	EnergyPak 4A smart charger compact
РАМКА	
<b>РАМКА</b>	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
<b>ВИЛКА</b>	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
<b>ЗАДЕН АМОРТИСЬОР</b>	N/A
КОМПОНЕНТИ	
<b>КОРМИЛО</b>	Giant Contact TR35, 20mm rise, 35mm
<b>ГРИПОВЕ</b>	Giant Tactal Pro single lock-on
<b>ЛАПА</b>	Giant Contact SL 35
<b>КОЛЧЕ ЗА СЕДАЛКА</b>	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
<b>СЕДАЛКА</b>	Giant Ergo Contact Trail
<b>ПЕДАЛИ</b>	platform
DRIVETRAIN	
<b>КОМАНДИ</b>	Shimano Deore, 1x10
<b>ПРЕДЕН ДЕРАЙЛЪОР</b>	co-moulded chain guide
<b>ЗАДЕН ДЕРАЙЛЪОР</b>	Shimano CUES RD-U6000, LinkGlide
<b>СПИРАЧКИ</b>	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
<b>КАСЕТА</b>	Shimano CUES LinkGlide, 10-speed, 11x48
<b>ВЕРИГА</b>	KMC eGlide, e-bike optimized
<b>КУРБЕЛ</b>	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
<b>СРЕДНА КАСЕТА</b>	N/A

КАПЛИ	
<b>ШИНИ</b>	Giant FT85C alloy, 27.5", 75mm
<b>ГЛАВИНИ</b>	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
<b>СПИЦИ</b>	stainless
<b>ГУМИ</b>	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
<b>ЕКСТРИ</b>	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

## ГЕОМЕТРИЯ

РАМКА	S	M	L	XL
Seat Tube Length (mm)	380	420	460	500
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650
Head Tube Length (mm)	110	120	135	150
Head Tube Angle	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	60	60	60	60
Trail (mm)	98,5	98,5	98,5	98,5
Wheelbase (mm)	1198	1220	1241	1263
Chain Stay Length (mm)	490	490	490	490
Bottom Bracket Drop (mm)	65	65	65	65
Stack (mm)	612	626	640	654
Обсер (mm)	426	442	458	474
Stand Over Height (mm)	750	780	815	835
Ширина на Кормило (mm)	780	780	780	780
Дължина на Лапа (mm)	40	40	50	50
Дължина на Курбел (mm)	165	165	165	165
Размер на Каплите	27.5"	27.5"	27.5"	27.5"

All specifications listed are subject to change without notice.