



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2, 85Nm, powered by Yamaha
KONTROLLER	RideControl Ergo, 5 power levels plus Smart Assist auto mode
DISPLAY	N/A
BATTERI	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
LADER	EnergyPak 4A smart charger compact
RAMME	
STØRRELSER	S, M, L, XL
FARVER	Space Grey
RAMME	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
FORGAFFEL	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
BAGDÆMPER	N/A
KOMponenter	
STYR	Giant Contact TR35, 20mm rise, 35mm
GREB / STYRBÅND	Giant Tactal Pro single lock-on
FREMPIND	Giant Contact SL 35
SADELPIND	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SADEL	Giant Ergo Contact Trail
PEDALER	platform
GEARGRUPPE	
SKIFTEGREB	Shimano Deore, 1x10
FORSKIFTER	co-moulded chain guide
BAGSKIFTER	Shimano CUES RD-U6000, LinkGlide
BREMSER	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
KASSETTE	Shimano CUES LinkGlide, 10-speed, 11x48
KÆDE	KMC eGlide, e-bike optimized
KRANKSÆT	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
KRANKBOKS	N/A

HJUL	
FÆLGE	Giant FT85C alloy, 27.5", 75mm
NAV	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
EGER	stainless
DÆK	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
EKSTRA	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

Pris: 33.999,00 kr.

GEOMETRI

RAMME	S	M	L	XL
Sadelrørlængde (mm)	380	420	460	500
Sadelrørsvinkel	75,0°	75,0°	75,0°	75,0°
Overrørlængde (mm)	590	610	630	650
Kronrørlængde (mm)	110	120	135	150
Kronrørsvinkel	68,0°	68,0°	68,0°	68,0°
Forgaffel fremspring (rake) (mm)	60	60	60	60
Sti (mm)	98,5	98,5	98,5	98,5
Akselafstand (mm)	1198	1220	1241	1263
Kædestagslængde (mm)	490	490	490	490
Krankboks drop (mm)	65	65	65	65
Stack (mm)	612	626	640	654
Reach (mm)	426	442	458	474
Skridthøjde (mm)	750	780	815	835
Styrbredde (mm)	780	780	780	780
Frempindslængde (mm)	40	40	50	50
Pedalarmslængde (mm)	165	165	165	165
Hjulstørrelse	27.5"	27.5"	27.5"	27.5"

Alle de anførte specifikationer kan ændres uden varsel.