



## SPECS

| HYBRID CYCLING TECHNOLOGY  |   |
|----------------------------|---|
| <b>MOTOR</b>               | SyncDrive Pro2, 85Nm, powered by Yamaha   |
| <b>CONTROLLER</b>          | RideControl Ergo, 5 power levels plus Smart Assist auto mode  |
| <b>DISPLAY</b>             | N/A   |
| <b>BATTERY</b>             | EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode |
| <b>CHARGER</b>             | EnergyPak 4A smart charger compact  |
| ΣΚΕΛΕΤΟΣ                   |   |
| <b>ΣΚΕΛΕΤΟΣ</b>            | ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount   |
| <b>ΠΙΠΟΥΝΙ</b>             | Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression  |
| <b>ΑΝΑΡΤΗΣΗ</b>            | N/A   |
| ΕΞΑΡΤΗΜΑΤΑ                 |   |
| <b>ΤΙΜΟΝΙ</b>              | Giant Contact TR35, 20mm rise, 35mm   |
| <b>GRIPS</b>               | Giant Tactal Pro single lock-on   |
| <b>ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ</b>     | Giant Contact SL 35   |
| <b>ΛΑΙΜΟΣ ΣΕΛΛΑΣ</b>       | Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]                  |
| <b>ΣΕΛΛΑ</b>               | Giant Ergo Contact Trail  |
| <b>ΠΕΝΤΑΛ</b>              | platform  |
| ΜΕΤΑΔΟΣΗ                   |   |
| <b>ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ</b>     | Shimano Deore, 1x10   |
| <b>ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ</b> | co-moulded chain guide  |
| <b>ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ</b>   | Shimano CUES RD-U6000, LinkGlide  |
| <b>ΦΡΕΝΑ</b>               | SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm  |
| <b>CASETTE Ή ΕΛΕΥΘΕΡΟ</b>  | Shimano CUES LinkGlide, 10-speed, 11x48   |
| <b>ΑΛΥΣΙΔΑ</b>             | KMC eGlide, e-bike optimized  |
| <b>ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ</b>      | Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms   |
| <b>BOTTOM BRACKET</b>      | N/A   |

| WHEELS          |  |
|-----------------|--|
| <b>ΣΤΕΦΑΝΙΑ</b> | Giant FT85C alloy, 27.5", 75mm   |
| <b>ΚΕΝΤΡΑ</b>   | Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]  |
| <b>ΑΚΤΙΝΕΣ</b>  | stainless  |
| <b>ΕΛΑΣΤΙΚΑ</b> | Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI  |
| <b>EXTRAS</b>   | Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable |

## ΓΕΩΜΕΤΡΙΑ

| ΣΚΕΛΕΤΟΣ                 | S     | M     | L     | XL    |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 380   | 420   | 460   | 500   |
| Seat Tube Angle          | 75,0° | 75,0° | 75,0° | 75,0° |
| Top Tube Length (mm)     | 590   | 610   | 630   | 650   |
| Head Tube Length (mm)    | 110   | 120   | 135   | 150   |
| Head Tube Angle          | 68,0° | 68,0° | 68,0° | 68,0° |
| Fork Rake (mm)           | 60    | 60    | 60    | 60    |
| Trail (mm)               | 98,5  | 98,5  | 98,5  | 98,5  |
| Wheelbase (mm)           | 1198  | 1220  | 1241  | 1263  |
| Chain Stay Length (mm)   | 490   | 490   | 490   | 490   |
| Bottom Bracket Drop (mm) | 65    | 65    | 65    | 65    |
| Stack (mm)               | 612   | 626   | 640   | 654   |
| Reach (mm)               | 426   | 442   | 458   | 474   |
| Stand Over Height (mm)   | 750   | 780   | 815   | 835   |
| Handlebar Width (mm)     | 780   | 780   | 780   | 780   |
| Stem Length (mm)         | 40    | 40    | 50    | 50    |
| Crank Length (mm)        | 165   | 165   | 165   | 165   |
| Wheel Size               | 27.5" | 27.5" | 27.5" | 27.5" |

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση