

YUKON E+



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	SyncDrive Pro2, 85Nm, powered by Yamaha
OHJAUSYKSIKKÖ	RideControl Ergo, 5 power levels plus Smart Assist auto mode
NÄYTTÖ	N/A
AKKU	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
LATURI	EnergyPak 4A smart charger compact
RUNKO	
RUNKO	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
HAARUKKA	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
ISKUNVAIMENNIN	N/A
KOMONENTIT	
OHJAUSTANKO	Giant Contact TR35, 20mm rise, 35mm
GRIPIT	Giant Tactal Pro single lock-on
OHJAINKANNATIN	Giant Contact SL 35
SATULATOLPPA	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SATULA	Giant Ergo Contact Trail
POLKIMET	platform
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore, 1x10
ETUVAIHTAJA	co-moulded chain guide
TAKAVAIHTAJA	Shimano CUES RD-U6000, LinkGlide
JARRUT	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
RATASPAKKA	Shimano CUES LinkGlide, 10-speed, 11x48
KETJUT	KMC eGlide, e-bike optimized
KAMPISARJA	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
KESKIÖ	N/A

RENKAAT	
VANTEET	Giant FT85C alloy, 27.5", 75mm
NAVAT	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
PINNAT	stainless
RENKAAT	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
LISÄTIEDOT	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

Suositusinta: 4 599,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	380	420	460	500
Satulaputken kulma	75,0°	75,0°	75,0°	75,0°
Vaakaputken pituus (mm)	590	610	630	650
Emäputken pituus (mm)	110	120	135	150
Emäputken kulma	68,0°	68,0°	68,0°	68,0°
Haarukan offset (mm)	60	60	60	60
Trail-mitta (mm)	98,5	98,5	98,5	98,5
Akseliväli (mm)	1198	1220	1241	1263
Takahaarukan alaputken pituus (mm)	490	490	490	490
Keskiön pudotus (mm)	65	65	65	65
Stack-mitta (mm)	612	626	640	654
Reach-mitta (mm)	426	442	458	474
Standover-mitta (mm)	750	780	815	835
Ohjaustangon leveys (mm)	780	780	780	780
Ohjainkannattimen pituus (mm)	40	40	50	50
Kammen pituus (mm)	165	165	165	165
Rengaskoko	27.5"	27.5"	27.5"	27.5"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.