

# YUKON E+



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDrive Pro2, 85Nm, powered by Yamaha
<b>CONTROLLER</b>	RideControl Ergo, 5 power levels plus Smart Assist auto mode
<b>DISPLAY</b>	N/A
<b>BATTERY</b>	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
<b>CHARGER</b>	EnergyPak 4A smart charger compact
FRAME	
<b>FRAME</b>	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
<b>FORK</b>	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 20mm rise, 35mm
<b>GRIPS</b>	Giant Tactal Pro single lock-on
<b>STEM</b>	Giant Contact SL 35
<b>SEATPOST</b>	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
<b>SADDLE</b>	Giant Ergo Contact Trail
<b>PEDALS</b>	platform
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore, 1x10
<b>FRONT DERAILLEUR</b>	co-moulded chain guide
<b>REAR DERAILLEUR</b>	Shimano CUES RD-U6000, LinkGlide
<b>BRAKES</b>	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
<b>CASSETTE</b>	Shimano CUES LinkGlide, 10-speed, 11x48
<b>CHAIN</b>	KMC eGlide, e-bike optimized
<b>CRANKSET</b>	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
<b>BOTTOM BRACKET</b>	N/A

WHEELS	
<b>RIMS</b>	Giant FT85C alloy, 27.5", 75mm
<b>HUBS</b>	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
<b>SPOKES</b>	stainless
<b>TIRES</b>	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
<b>EXTRAS</b>	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

**Suggested Retail Price (CDN): \$6,499.00**

## FRAME GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	380	420	460	500
Seat Tube Angle	75.0°	75.0°	75.0°	75.0°
Top Tube Length (mm)	590	610	630	650
Head Tube Length (mm)	110	120	135	150
Head Tube Angle	68.0°	68.0°	68.0°	68.0°
Fork Rake (mm)	60	60	60	60
Trail (mm)	98.5	98.5	98.5	98.5
Wheelbase (mm)	1198	1220	1241	1263
Chain Stay Length (mm)	490	490	490	490
Bottom Bracket Drop (mm)	65	65	65	65
Stack (mm)	612	626	640	654
Reach (mm)	426	442	458	474
Stand Over Height (mm)	750	780	815	835
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	27.5"	27.5"	27.5"	27.5"

*All prices and specifications are subject to change without notice.*