



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Pro2, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo, 5 power levels plus Smart Assist auto mode
PRIKAZ	N/A
BATERIJA	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
CHARGER	EnergyPak 4A smart charger compact
OKVIR	
OKVIR	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
VILICA	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact TR35, 20mm rise, 35mm
GRIPS	Giant Tactal Pro single lock-on
LULA VOLANA	Giant Contact SL 35
CIJEV SJEDALA	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SJEDALO	Giant Ergo Contact Trail
PEDALE	platform
POGON	
RUČICE MJENJAČA	Shimano Deore, 1x10
PREDNJI MJENJAČ	co-moulded chain guide
STRAŽNJI MJENJAČ	Shimano CUES RD-U6000, LinkGlide
KOČNICE	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
KAZETA	Shimano CUES LinkGlide, 10-speed, 11x48
LANAC	KMC eGlide, e-bike optimized
POGON	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
OSOVINA POGONA (BB)	N/A

KOTAČI	
OBRUČI	Giant FT85C alloy, 27.5", 75mm
NABE	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
ŽBICE	stainless
GUME	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
DODACI	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	S	M	L	XL
Dužina cijevi sjedala (mm)	380	420	460	500
Kut cijevi sjedala	75,0°	75,0°	75,0°	75,0°
Dužina gornje cijevi (mm)	590	610	630	650
Dužina prednje cijevi (mm)	110	120	135	150
Kut vilice	68,0°	68,0°	68,0°	68,0°
Zakrivljenost vilice (offset) (mm)	60	60	60	60
Staza (mm)	98,5	98,5	98,5	98,5
Međuosovinski razmak kotača (mm)	1198	1220	1241	1263
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	490	490	490	490
Položaj osovine pogona (mm)	65	65	65	65
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	612	626	640	654
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	426	442	458	474
Prekoračna visina (mm)	750	780	815	835
Širina volana (mm)	780	780	780	780
Dužina lule volana (mm)	40	40	50	50
Dužina poluge pedale (mm)	165	165	165	165
Veličina kotača	27.5"	27.5"	27.5"	27.5"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.