



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo, 5 power levels plus Smart Assist auto mode
DISPLAY	N/A
BATTERY	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
CHARGER	EnergyPak 4A smart charger compact
CADRU	
CADRU	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
FURCA	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
SOC	N/A
COMPONENTE	
GHIDON	Giant Contact TR35, 20mm rise, 35mm
GRIPS	Giant Tactal Pro single lock-on
PIPA	Giant Contact SL 35
TIJA SA	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SA	Giant Ergo Contact Trail
PEDALE	platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore, 1x10
SCHIMBATOR FATA	co-moulded chain guide
SCHIMBATOR SPATE	Shimano CUES RD-U6000, LinkGlide
FRANE	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
PINIOANE	Shimano CUES LinkGlide, 10-speed, 11x48
LANT	KMC eGlide, e-bike optimized
ANGRENAJ	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
BOTTOM BRACKET	N/A

ROTI	
JANTE	Giant FT85C alloy, 27.5", 75mm
BUTUCI	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
SPITE	stainless
ANVELOPE	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
EXTRAS	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

GEOMETRIE

CADRU	S	M	L	XL
Seat Tube Length (mm)	380	420	460	500
Seat Tube Angle	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650
Head Tube Length (mm)	110	120	135	150
Head Tube Angle	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	60	60	60	60
Trail (mm)	98,5	98,5	98,5	98,5
Wheelbase (mm)	1198	1220	1241	1263
Chain Stay Length (mm)	490	490	490	490
Bottom Bracket Drop (mm)	65	65	65	65
Stack (mm)	612	626	640	654
Reach (mm)	426	442	458	474
Stand Over Height (mm)	750	780	815	835
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	165	165
Wheel Size	27.5"	27.5"	27.5"	27.5"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.