



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Pro2, 85Nm, powered by Yamaha
TIPALO	RideControl Ergo, 5 power levels plus Smart Assist auto mode
PRIKAZOVALNIK	N/A
BATERIJA	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
CHARGER	EnergyPak 4A smart charger compact
OKVIR	
OKVIR	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
VILICE	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact TR35, 20mm rise, 35mm
GRIPS	Giant Tactal Pro single lock-on
OPORA KRMILA	Giant Contact SL 35
OPORA SEDEŽA	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SEDEŽ	Giant Ergo Contact Trail
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano Deore, 1x10
PREDNJI MENJALNIK	co-moulded chain guide
ZADNJI MENJALNIK	Shimano CUES RD-U6000, LinkGlide
ZAVORE	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
VERIŽNIK	Shimano CUES LinkGlide, 10-speed, 11x48
VERIGA	KMC eGlide, e-bike optimized
GONILKE Z VERIŽNIKI	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
BOTTOM BRACKET	N/A

OBROČNIKI

OBROČI	Giant FT85C alloy, 27.5", 75mm
PESTA	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
NAPERE	stainless
PLAŠČI	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
DODATKI	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	380	420	460	500
Kot sedežne cevi	75,0°	75,0°	75,0°	75,0°
Top Tube Length (mm)	590	610	630	650
Višina glave okvirja (mm)	110	120	135	150
Krmični kot	68,0°	68,0°	68,0°	68,0°
Zamik vpetja osi (mm)	60	60	60	60
Trail (mm)	98,5	98,5	98,5	98,5
Medosna razdalja (mm)	1198	1220	1241	1263
Dolžina cevi ob verigi (mm)	490	490	490	490
Bottom Bracket Drop (mm)	65	65	65	65
Oddaljenost zgornje cevi od gonilne osi (mm)	612	626	640	654
Doseg (mm)	426	442	458	474
Višina zgornje cevi (mm)	750	780	815	835
Širina krmila (mm)	780	780	780	780
Dolžina opore krmila (mm)	40	40	50	50
Dolžina gonilke (mm)	165	165	165	165
Velikost obročnikov	27.5"	27.5"	27.5"	27.5"

Vse navedene specifikacije se lahko spremenijo brez obvestila.