



## SPECS

HYBRID CYKELTEKNIK	
MOTOR	SyncDrive Pro2, 85Nm, powered by Yamaha
KONTROLLER	RideControl Ergo, 5 power levels plus Smart Assist auto mode
VISA	N/A
BATTERI	EnergyPak Smart 800Wh, alloy casing with highest safety standard (EN50604), CO2 neutral production, EnergyPak Plus 200Wh range extender compatible, low temperature protection mode
LADDARE	EnergyPak 4A smart charger compact
RAM	
RAM	ALUXX aluminum, Overdrive head tube, 12x197mm thru-axle, integrated KS40 kickstand mount, M10 trailer mount
GAFFEL	Manitou Mastodon Comp - Gen 3, 27.5", 100mm, Expert Air, Absolute+ compression
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact TR35, 20mm rise, 35mm
GREPPAR	Giant Tactal Pro single lock-on
STAM	Giant Contact SL 35
SADELSTOLPE	Giant Contact Switch AT Adjustable dropper, remote [S: 110-140mm travel / 30.9 x 395mm, M: 140-170mm travel / 30.9 x 470mm, L/XL: 170-200mm travel / 30.9 x 530mm]
SADEL	Giant Ergo Contact Trail
PEDALER	platform
DRIVLINA	
VÄXLAR	Shimano Deore, 1x10
FRAMVÄXEL	co-moulded chain guide
BAKVÄXEL	Shimano CUES RD-U6000, LinkGlide
BROMSAR	SRAM Code R, 4-piston hydraulic, SRAM Centerline rotors [F] 180mm, [R] 180mm
KASSETT	Shimano CUES LinkGlide, 10-speed, 11x48
KEDJA	KMC eGlide, e-bike optimized
VEVPARTI	Forged alloy spider BCD 104, steel narrow/wide chainring 36T Forged aluminum crank arms
BROMSREGLAGE	N/A

HJUL	
FÄLGAR	Giant FT85C alloy, 27.5", 75mm
NAV	Giant alloy 6-bolt disc sealed bearing, 15x150mm [F] 12x197mm [R]
EKRAR	stainless
DÄCK	Vee Tire Co. Avalanche, 27.5x4.5", SC compound, folding, tubeless, studdable, 120 TPI
EXTRAFUNKTIONER	Stud kit (500) with tool, tubeless kit (valves, levers, tool) (inner tube supplied), 4.5" max tire size. Optional: Giant Recon series e-bike lights available and direct connectable

Price: 51 990,00 kr

## GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	380	420	460	500
Vinkel sadelrör	75,0°	75,0°	75,0°	75,0°
Topprörets längd (mm)	590	610	630	650
Styrhuvud Längd (mm)	110	120	135	150
Vinkel styrhuvud	68,0°	68,0°	68,0°	68,0°
Gaffelvinkel (mm)	60	60	60	60
Spår (mm)	98,5	98,5	98,5	98,5
Hjulbas (mm)	1198	1220	1241	1263
Kedjestagslängd (mm)	490	490	490	490
Nedre fäste Drop (mm)	65	65	65	65
Stack (mm)	612	626	640	654
Reach (mm)	426	442	458	474
Stå över höjden (mm)	750	780	815	835
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	40	40	50	50
Vevlängd (mm)	165	165	165	165
Hjulstorlek	27.5"	27.5"	27.5"	27.5"

All specifications listed are subject to change without notice.