

랑마 어드밴스 프로 0 QOM



스펙

프레임	
사이즈	XXS, XS, S
색상	Ocean Twilight/Chrome
프레임	Advanced-Grade Composite, 12x142mm thru-axle, disc
포크	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
부품	
핸들바	Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
스템	Giant Contact SL AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
시프스트	Giant Variant, composite, -5/+15mm offset
안장	Liv Alacra SL
구동계	
변속기	Shimano Ultegra Di2
앞 변속기	Shimano Ultegra Di2 FD-R8150
뒷 변속기	Shimano Ultegra Di2 RD-R8150
브레이크	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
브레이크 레버	Shimano Ultegra Di2
스프라켓	Shimano Ultegra, 12-speed, 11x34
체인	Shimano CN-M8100
크랭크 셋	Shimano Ultegra, 34/50 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BB	Shimano, press fit

바퀴	
휠	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
허브	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
스포크	Giant Aero Carbon Spoke
타이어	CADEX Race GC, tubeless, 700x28c (28mm), folding
추가 기능	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
최대 타이어 클리어런스	33mm

가격: ₩7,890,000

지오메트리

프레임	XXS	XS	S
시트 튜브 길이 (mm)	390	420	450
시트 튜브 각도	75.0°	75.0°	74.5°
탐튜브 길이 (mm)	498	508	524
헤드 튜브 길이 (mm)	105	120	135
헤드 튜브 각도	70.0°	71.0°	72.0°
포크 레이크 (mm)	49	49	49
트레일 (mm)	74	68	61
휠베이스 (mm)	970	973	977
체인스테이 길이 (mm)	405	405	405
BB (mm)	72	72	69.5
스택 (mm)	499	517	532
범위 (mm)	364	370	377
스탠드 오버 (mm)	685	707	736
핸들바 폭 (mm)	360	360	380
스템 길이 (mm)	80	80	90
크랭크 길이 (mm)	165	165	170
휠사이즈	700C	700C	700C

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.