

디보트 어드밴스 2



스펙

프레임	
사이즈	XS, S
색상	Lunar Eclipse
프레임	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
포크	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
서스펜션	N/A
부품	
핸들바	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
스템	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
싯포스트	Giant D-Fuse, composite, 14mm offset
안장	Liv Grit
구동계	
변속기	Shimano GRX RX-610, 2x12
앞 변속기	Shimano GRX RX-820
뒷 변속기	Shimano GRX RX-820
브레이크	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
브레이크 레버	Shimano GRX RX-610 hydraulic
스프라켓	Shimano CS-HG710, 12-speed, 11x36
체인	KMC X12L-1
크랭크 셋	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BB	Shimano, press fit

바퀴	
립	Giant P-X2 Disc, alloy
허브	Giant alloy, 12mm thru-axle
스포크	Sapim
타이어	Giant Crosscut Grip, 700x45c, tubeless
추가 기능	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
최대 타이어 클리어런스	53mm

가격: ₩2,690,000

지오메트리

프레임	XS		S	
	SHORT	LONG	SHORT	LONG
시트 튜브 길이 (mm)	390	420	420	420
시트 튜브 각도	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
탐튜브 길이 (mm)	525 525	535 535	535 535	535 535
헤드 튜브 길이 (mm)	90	110	110	110
헤드 튜브 각도	70.0° 69.9°	70.5° 70.4°	70.5° 70.4°	70.5° 70.4°
포크 레이크 (mm)	50	50	50	50
트레일 (mm)	78.4 82	75 78.5	75 78.5	75 78.5
휠베이스 (mm)	1012 1022	1019 1029	1019 1029	1019 1029
체인스테이 길이 (mm)	425 435	425 435	425 435	425 435
BB (mm)	80 81	80 81	80 81	80 81
스택 (mm)	523 524	544 545	544 545	544 545
범위 (mm)	380 379	384 383	384 383	384 383
스탠드 오버 (mm)	681 688	708 715	708 715	708 715
핸들바 폭 (mm)	400	400	400	400
스템 길이 (mm)	50	60	60	60
크랭크 길이 (mm)	165	170	170	170

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.