엔비리브 어드밴스 2



스펙

프레임	
사이즈	XXS, XS, S, M, L
색상	Midnight Pine, Desert Pearl
프레임	Advanced-grade composite, 12x142mm thru-axle, disc
포크	Advanced-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
부품	
핸들바	Liv Contact SL Aero, 31.8mm, 72mm reach, 125mm drop XXS: 340/360mm, XS: 340/360mm, S: 360/380mm, M: 370/400mm, L: 390/420mm
GRIPS	Liv Stratus Lite 2.0
스템	Liv Contact SL Aero, -10-degree XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
싯포스트	Giant Vector, composite, -5/ +15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
안장	Liv Alacra SL
구동계	
변속기	Shimano 105
앞 변속기	Shimano 105
뒷 변속기	Shimano 105
브레이크	Shimano 105 hydraulic, Shimano SM-RT64 [F]160mm, [R]140mm
브레이크 레버	Shimano 105 hydraulic
스프라켓	Shimano 105, 12-speed, 11x36
체인	KMC X12L-1
크랭크 셋	Shimano 105, 36/52 XXS:160mm, XS:165mm, S:165mm, M:170mm, L:17omm
BB	Shimano, press fit

바퀴	
림	Giant P-A1 Disc, alloy
허브	Giant P-A1 Disc, 12mm thru-axle
스포크	stainless
타이어	Giant Gavia Course, 700x28c, folding, tubeless
추가 기능	computer mount, tubeless prepared, two aero bottle cages, 32mm max tire size, UDH compatible

가격: ₩3,690,000

지오메트리

프레임	XXS	XS	S
시트 튜브 길이 (mm)	446.5	465	498
시트 튜브 각도	75.0°	75.0°	74.5°
탑튜브 길이 (mm)	504	514.8	526.2
헤드 튜브 길이 (mm)	100	115	130
헤드튜브 각도	70.0°	71.0°	72.0°
포크 레이크 (mm)	49	49	49
트레일 (mm)	73.2	66.8	60.4
휠베이스 (mm)	969.9	974.7	977
체인스테이 길이 (mm)	405	405	405
BB (mm)	72	72	70
스택 (mm)	494.1	511.8	527
범위 (mm)	365.6	372.9	377.8
스탠드 오버 (mm)	714.8	732.6	760.8
핸들바 폭 (mm)	360	380	380
스템 길이 (mm)	80	80	90
크랭크 길이 (mm)	160	165	165

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.