

ALIGHT 3



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Gloss Ocean Wave
FRAME	ALUXX-grade aluminium
FORK	High-tensile steel
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Sport flat, 25.4mm, 20mm riser
GRIPS	Liv Connect Ergo
STEM	Giant Sport, 25.4mm
SEATPOST	Giant Sport, alloy, 27.2mm
SADDLE	Liv Sport
PEDALS	Platform pedal
DRIVETRAIN	
SHIFTERS	Shimano Tourney, 3x7
FRONT DERAILLEUR	Shimano Tourney
REAR DERAILLEUR	Shimano Tourney
BRAKES	Tektro TK837, alloy, linear pull
BRAKE LEVERS	Shimano EF41
CASSETTE	Shimano MF-TZ500, 14x34
CHAIN	KMC Z7
CRANKSET	ProWheel TY-CQ99, 28/38/48
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant GX06 alloy
HUBS	Giant alloy, QR
SPOKES	Stainless steel
TYRES	Giant S-X3, puncture protect, 700x38c
EXTRAS	N/A
LIMITS	
MAX TYRE CLEARANCE	40mm

Price: £499.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	370	420	460	500
Seat Tube Angle	73.5°	73.5°	73.0°	73.0°
Top Tube Length (mm)	545	560	575	590
Head Tube Length (mm)	145	160	180	200
Head Tube Angle	70.0°	70.5°	71.0°	71.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	75.6	72.3	69	69.2
Wheelbase (mm)	1035	1046	1046	1056
Chain Stay Length (mm)	445	445	445	445
Bottom Bracket Drop (mm)	62	62	62	62
Stack (mm)	568	585	606	624
Reach (mm)	357	367	365	369
Stand Over Height (mm)	683	719	749	779
Handlebar Width (mm)	600	600	640	640
Stem Length (mm)	80	80	90	100
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.