

# ALIGHT 3



## SPECS

| FRAME            |                                      |
|------------------|--------------------------------------|
| SIZES            | XS, S, M, L                          |
| COLOURS          | Gloss Ocean Wave                     |
| FRAME            | ALUXX-grade aluminium                |
| FORK             | High-tensile steel                   |
| SHOCK            | N/A                                  |
| COMPONENTS       |                                      |
| HANDLEBAR        | Giant Sport flat, 25.4mm, 20mm riser |
| GRIPS            | Liv Connect Ergo                     |
| STEM             | Giant Sport, 25.4mm                  |
| SEATPOST         | Giant Sport, alloy, 27.2mm           |
| SADDLE           | Liv Sport                            |
| PEDALS           | Platform pedal                       |
| DRIVETRAIN       |                                      |
| SHIFTERS         | Shimano Tourney, 3x7                 |
| FRONT DERAILLEUR | Shimano Tourney                      |
| REAR DERAILLEUR  | Shimano Tourney                      |
| BRAKES           | Tektro TK837, alloy, linear pull     |
| BRAKE LEVERS     | Shimano EF41                         |
| CASSETTE         | Shimano MF-TZ500, 14x34              |
| CHAIN            | KMC Z7                               |
| CRANKSET         | ProWheel TY-CQ99, 28/38/48           |
| BOTTOM BRACKET   | cartridge                            |

| WHEELS |                                       |
|--------|---------------------------------------|
| RIMS   | Giant GX06 alloy                      |
| HUBS   | Giant alloy, QR                       |
| SPOKES | Stainless steel                       |
| TYRES  | Giant S-X3, puncture protect, 700x38c |
| EXTRAS | 40mm, max tyre size                   |

Price: €569.00

## GEOMETRY

| FRAME                    | XS    | S     | M     | L     |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 370   | 420   | 460   | 500   |
| Seat Tube Angle          | 73.5° | 73.5° | 73.0° | 73.0° |
| Top Tube Length (mm)     | 545   | 560   | 575   | 590   |
| Head Tube Length (mm)    | 145   | 160   | 180   | 200   |
| Head Tube Angle          | 70.0° | 70.5° | 71.0° | 71.0° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    |
| Trail (mm)               | 75.6  | 72.3  | 69    | 69.2  |
| Wheelbase (mm)           | 1035  | 1046  | 1046  | 1056  |
| Chain Stay Length (mm)   | 445   | 445   | 445   | 445   |
| Bottom Bracket Drop (mm) | 62    | 62    | 62    | 62    |
| Stack (mm)               | 568   | 585   | 606   | 624   |
| Reach (mm)               | 357   | 367   | 365   | 369   |
| Stand Over Height (mm)   | 683   | 719   | 749   | 779   |
| Handlebar Width (mm)     | 600   | 600   | 640   | 640   |
| Stem Length (mm)         | 80    | 80    | 90    | 100   |
| Crank Length (mm)        | 165   | 165   | 170   | 170   |
| Wheel Size               | 700C  | 700C  | 700C  | 700C  |

All specifications listed are subject to change without notice.