



СПЕЦИФИКАЦИИ

| ХИБРИДНА ТЕХНОЛОГИЯ ЗА КОЛОЕЗДЕНЕ | |
|-----------------------------------|--|
| МОТОР | Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology |
| КОНТРОЛЕР | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels |
| ДИСПЛЕЙ | Giant RideControl Dash 2, high-angle visibility, full color LCD display |
| БАТЕРИЯ | Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| ЗАРЯДНО | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| РАМКА | |
| РАЗМЕР | XS, S, M, L |
| ЦВЯТ | Ocean Twilight, Misty Lilac |
| РАМКА | ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount |
| ВИЛКА | SR Suntour NVX32 coil 29" 63mm travel 15x100 AH axle |
| ЗАДЕН АМОРТИСЬОР | n/a |
| КОМПОНЕНТИ | |
| КОРМИЛО | Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm |
| ГРИПОВЕ | Liv Comfort Ergo Microtech Plus |
| ЛАПА | Aluminum angle adjustable stem |
| КОЛЧЕ ЗА СЕДАЛКА | Suspension 2-bolt micro-adjustable, 30,9mm |
| СЕДАЛКА | Selle Royal Lift |
| ПЕДАЛИ | Anti-slip Platform |
| DRIVETRAIN | |
| КОМАНДИ | Shimano Cues 9-speed |
| ЗАДЕН ДЕРАЙЛЪОР | Shimano Cues 9-speed |
| СПИРАЧКИ | Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R] |
| РЪКОХВАТКИ ЗА СПИРАЧКИ | Tektro HD-M281 |
| КАСЕТА | Shimano Cues 11-36T, 9-speed |
| ВЕРИГА | KMC E9 Sport NP/БК, e-bike optimized |
| КУРБЕЛ | Aluminum 38T |

| КАПЛИ | |
|-----------------|---|
| ШИНИ | Liv GX03V 700c aluminium |
| ГЛАВИНИ | Shimano center-lock 15x100mm [F], Shimano center-lock OLD 135mm [R] |
| СПИЦИ | Stainless steel |
| ГУМИ | Maxxis MetroPass 28x2.2 |
| АКСЕСОАРИ | |
| СВЕТЛИНИ | Recon E HL50 StZVO [F] Аxa BlueLine Steady E6 [R] |
| КАТИНАРИ | ABUS Xplus battery lock |
| БАГАЖНИК | MIK System rack. Child seat, bag & basket compatible |

ГЕОМЕТРИЯ

| РАМКА | XS | S | M | L |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 380 | 430 | 460 | 495 |
| Seat Tube Angle | 74,0° | 73,5° | 73,0° | 72,5° |
| Top Tube Length (mm) | 565 | 580 | 600 | 620 |
| Head Tube Length (mm) | 180 | 180 | 200 | 200 |
| Head Tube Angle | 69,5° | 69,5° | 69,5° | 69,5° |
| Fork Rake (mm) | 46 | 46 | 46 | 46 |
| Trail (mm) | 94,5 | 94,5 | 94,5 | 94,5 |
| Wheelbase (mm) | 1116 | 1137 | 1152 | 1165 |
| Chain Stay Length (mm) | 482 | 482 | 482 | 482 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 | 60 |
| Stack (mm) | 662 | 662 | 681 | 681 |
| Обсер (mm) | 366 | 384 | 392 | 405 |
| Stand Over Height (mm) | 427 | 428 | 431 | 437 |
| Ширина на Кормило (mm) | 660 | 660 | 660 | 660 |
| Дължина на Лапа (mm) | 80 | 80 | 100 | 100 |
| Дължина на Курбел (mm) | 165 | 165 | 170 | 170 |
| Размер на Каплите | 700C | 700C | 700C | 700C |

All specifications listed are subject to change without notice.