

ALLURE E+ 2



SPECS

| HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST) | |
|--|--|
| MOTOR | Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology |
| CONTROLLER | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels |
| DISPLAY | Giant RideControl Dash 2, high-angle visibility, full color LCD display |
| BATTERY | Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production |
| CHARGER | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| FRAME | |
| SIZES | XS, S, M |
| COLOURS | Ocean Twilight |
| FRAME | ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA40 kickstand mount |
| FORK | SR Suntour NVX32 coil 29" 63mm travel 15x100 AH axle |
| SHOCK | n/a |
| COMPONENTS | |
| HANDLEBAR | Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm |
| GRIPS | Liv Comfort Ergo Microtech Plus |
| STEM | Aluminum angle adjustable stem |
| SEATPOST | Suspension 2-bolt micro-adjustable, 30,9mm |
| SADDLE | Selle Royal Lift |
| PEDALS | Anti-slip Platform |
| DRIVETRAIN | |
| SHIFTERS | Shimano Cues 9-speed |
| REAR DERAILLEUR | Shimano Cues 9-speed |
| BRAKES | Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R] |
| BRAKE LEVERS | Tektro HD-M281 |
| CASSETTE | Shimano Cues 11-36T, 9-speed |
| CHAIN | KMC E9 Sport NP/BK, e-bike optimized |
| CRANKSET | Aluminum 38T |

| WHEELS | |
|-----------------|---|
| RIMS | Liv GX03V 700c aluminium |
| HUBS | Shimano center-lock 15x100mm [F], Shimano center-lock OLD 135mm [R] |
| SPOKES | Stainless steel |
| TYRES | Maxxis MetroPass 28x2.2 |
| ACCESSORIES | |
| LIGHTING | Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R] |
| LOCK | ABUS Xplus battery lock |
| CARRIER | MIK System rack. Child seat, bag & basket compatible |

Price: £2,599.00

GEOMETRY

| FRAME | XS | S | M |
|--------------------------|-------|-------|-------|
| Seat Tube Length (mm) | 380 | 430 | 460 |
| Seat Tube Angle | 74.0° | 73.5° | 73.0° |
| Top Tube Length (mm) | 565 | 580 | 600 |
| Head Tube Length (mm) | 180 | 180 | 200 |
| Head Tube Angle | 69.5° | 69.5° | 69.5° |
| Fork Rake (mm) | 46 | 46 | 46 |
| Trail (mm) | 94.5 | 94.5 | 94.5 |
| Wheelbase (mm) | 1116 | 1137 | 1152 |
| Chain Stay Length (mm) | 482 | 482 | 482 |
| Bottom Bracket Drop (mm) | 60 | 60 | 60 |
| Stack (mm) | 662 | 662 | 681 |
| Reach (mm) | 366 | 384 | 392 |
| Stand Over Height (mm) | 427 | 428 | 431 |
| Handlebar Width (mm) | 660 | 660 | 660 |
| Stem Length (mm) | 80 | 80 | 100 |
| Crank Length (mm) | 165 | 165 | 170 |
| Wheel Size | 700C | 700C | 700C |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.