

ALLURE E+ 2



SPECIFIKACIJE

| HIBRIDNA TEHNOLOGIJA | |
|-------------------------|--|
| MOTOR | Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology |
| SENSOR | Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels |
| PRIKAZ | Giant RideControl Dash 2, high-angle visibility, full color LCD display |
| BATERIJA | Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| CHARGER | Giant EnergyPak smart charger 4A |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| OKVIR | |
| VELIČINE | XS, S, M, L |
| BOJE | Ocean Twilight, Misty Lilac |
| OKVIR | ALUXX aluminum, Overdrive 1½ - 1¾" head tube, integrated KSA40 kickstand mount |
| VILICA | SR Suntour NVX32 coil 29" 63mm travel 15x100 AH axle |
| AMORTIZER | n/a |
| KOMPONENTE | |
| VOLAN | Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm |
| GRIPS | Liv Comfort Ergo Microtech Plus |
| LULA VOLANA | Aluminum angle adjustable stem |
| CIJEV SJEDALA | Suspension 2-bolt micro-adjustable, 30,9mm |
| SJEDALO | Selle Royal Lift |
| PEDALE | Anti-slip Platform |
| POGON | |
| RUČICE MJENJAČA | Shimano Cues 9-speed |
| STRAŽNJI MJENJAČ | Shimano Cues 9-speed |
| KOČNICE | Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R] |
| RUČICE KOČNICA | Tektro HD-M281 |
| KAZETA | Shimano Cues 11-36T, 9-speed |
| LANAC | KMC E9 Sport NP/BK, e-bike optimized |
| POGON | Aluminum 38T |

| KOTAČI | |
|----------------|---|
| OBRUČI | Liv GX03V 700c aluminium |
| NABE | Shimano center-lock 15x100mm [F], Shimano center-lock OLD 135mm [R] |
| ŽBICE | Stainless steel |
| GUME | Maxxis MetroPass 28x2.2 |
| DODACI | |
| SVJETLA | Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R] |
| LOKOTI | ABUS Xplus battery lock |
| NOSAČ | MIK System rack. Child seat, bag & basket compatible |

GEOMETRIJA

| OKVIR | XS | S | M | L |
|--|-------|-------|-------|-------|
| Dužina cijevi sjedala (mm) | 380 | 430 | 460 | 495 |
| Kut cijevi sjedala | 74,0° | 73,5° | 73,0° | 72,5° |
| Dužina gornje cijevi (mm) | 565 | 580 | 600 | 620 |
| Dužina prednje cijevi (mm) | 180 | 180 | 200 | 200 |
| Kut vilice | 69,5° | 69,5° | 69,5° | 69,5° |
| Zakrivljenost vilice (offset) (mm) | 46 | 46 | 46 | 46 |
| Staza (mm) | 94,5 | 94,5 | 94,5 | 94,5 |
| Međuosovinski razmak kotača (mm) | 1116 | 1137 | 1152 | 1165 |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm) | 482 | 482 | 482 | 482 |
| Položaj osovine pogona (mm) | 60 | 60 | 60 | 60 |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm) | 662 | 662 | 681 | 681 |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 366 | 384 | 392 | 405 |
| Prekoračna visina (mm) | 427 | 428 | 431 | 437 |
| Širina volana (mm) | 660 | 660 | 660 | 660 |
| Dužina lule volana (mm) | 80 | 80 | 100 | 100 |
| Dužina poluge pedale (mm) | 165 | 165 | 170 | 170 |
| Veličina kotača | 700C | 700C | 700C | 700C |

Sve navedene specifikacije podložne su promjeni bez prethodne najave.