ALLURE E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
CONTROLLER	RideControl Ergo 2, RideControl GO integrated in D/T
DISPLAY	RideDash Evo
BATTERY	EnergyPak Smart Compact 500Wh
FRAME	
SIZES	XS, S, M, L
COLORS	Grayish Blue, Desert Sage
FRAME	ALUXX Aluminum, Overdrive 1½ - 1⅛" head tube, integrated KS18 kickstand mount
FORK	SR Suntour NEX E25, 50mm
SHOCK	-
COMPONENTS	
HANDLEBAR	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Liv Comfort Ergo Microtech Plus
STEM	Giant Contour, EVO display integrated, adjustable
SEATPOST	Suspension 2-bolt micro-adjustable, 30.9x300mm [S, M, L] Forged aluminum 30.9x250mm [XS]
SADDLE	Selle Royal Lift
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano Nexus 7-speed RevoShift
FRONT DERAILLEUR	-
REAR DERAILLEUR	-
BRAKES	Tektro HD-M275, hydraulic disc, 160mm [F/R]
BRAKE LEVERS	Tektro HD-M276
CASSETTE	18T
CHAIN	KMX Z1e HX, e-bike optimized
CRANKSET	Aluminum, 38T
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Liv GX03V, 700c aluminium
HUBS	Shimano HB-MT200 9mm QR Disc [F], Shimano Nexus 7 Disc brake [R]
SPOKES	Stainless steel
TIRES	Maxxis Metro Pass 622x50, 60tpi, Wire Bead, Reflective, ECE-R75
EXTRAS	-
ACCESSORIES	
LIGHTING	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
LOCK	-
CARRIER	MIK HD rack. system bag & basket compatible

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	450	500	550
Seat Tube Angle	74,0°	73,5°	73,0°	72,5°
Top Tube Length (mm)	570	580	595	610
Head Tube Length (mm)	180	180	200	200
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9
Wheelbase (mm)	1127	1131	1141	1150
Chain Stay Length (mm)	480	480	480	480
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	646	646	665	665
Reach (mm)	385	389	392	400
Handlebar Width (mm)	630	630	670	670
Stem Length (mm)	90	90	90	90
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.