

ALLURE E+ 2



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
SENSOR	RideControl Ergo 2, RideControl GO integrated in D/T
DISPLAY	RideDash Evo
BATTERI	EnergyPak Smart Compact 500Wh
RAMME	
STØRRELSE	XS, S, M, L
FARGE	Grayish Blue, Desert Sage
RAMME	ALUXX Aluminum, Overdrive 1½ - 1½" head tube, integrated KS18 kickstand mount
GAFFEL	SR Suntour NEX E25, 50mm
DEMPER	-
KOMPONENTER	
STYRE	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Liv Comfort Ergo Microtech Plus
STYRSTEM	Giant Contour, EVO display integrated, adjustable
SETEPINNE	Suspension 2-bolt micro-adjustable, 30.9x300mm [S, M, L] Forged aluminum 30.9x250mm [XS]
SADEL	Selle Royal Lift
PEDALER	Aluminum Platform
DRIVVERK	
GIRHENDLER	Shimano Nexus 7-speed RevoShift
FRONTGIR	-
BAKGIR	-
BREMSER	Tektro HD-M275, hydraulic disc, 160mm [F/R]
BREMSEHENDLER	Tektro HD-M276
KASSETT	18T
KJEDE	KMX Z1e HX, e-bike optimized
KRANK	Aluminum, 38T
BOTTOM BRACKET	N/A

HJUL	
FELG	Liv GX03V, 700c aluminium
NAV	Shimano HB-MT200 9mm QR Disc [F], Shimano Nexus 7 Disc brake [R]
EIKE	Stainless steel
DEKK	Maxxis Metro Pass 622x50, 60tpi, Wire Bead, Reflective, ECE-R75
EXTRAS	-
TILBEHØR	
LYS	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
LÅS	-
BAGASJEBRETT	MIK HD rack. system bag & basket compatible

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	380	450	500	550
Seat Tube Angle	74,0°	73,5°	73,0°	72,5°
Top Tube Length (mm)	570	580	595	610
Head Tube Length (mm)	180	180	200	200
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9
Wheelbase (mm)	1127	1131	1141	1150
Chain Stay Length (mm)	480	480	480	480
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	646	646	665	665
Reach (mm)	385	389	392	400
Handlebar Width (mm)	630	630	670	670
Stem Length (mm)	90	90	90	90
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.