

# ALLURE E+ 2



## SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
<b>MOTOR</b>	Giant SyncDrive Sport2, 75Nm PedalPlus 6-sensor technology
<b>SENSOR</b>	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
<b>ECRÃ</b>	Giant RideControl Dash 2, high-angle visibility, full color LCD display
<b>BATERIA</b>	Giant EnergyPak Smart 430Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CARREGADOR</b>	Giant EnergyPak smart charger 4A
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
<b>TAMANHOS</b>	XS, S, M, L
<b>CORES</b>	Ocean Twilight
<b>QUADRO</b>	ALUXX aluminum, Overdrive 1½ - 1½" head tube, integrated KSA40 kickstand mount
<b>FORQUILHA</b>	SR Suntour NVX32 coil 29" 63mm travel 15x100 AH axle
<b>AMORTECEDORES</b>	n/a
COMPONENTES	
<b>GUIADOR</b>	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm
<b>PUNHOS</b>	Liv Comfort Ergo Microtech Plus
<b>AVANÇO</b>	Aluminum angle adjustable stem
<b>ESPIGÃO DE SELIM</b>	Suspension 2-bolt micro-adjustable, 30,9mm
<b>SELIM</b>	Selle Royal Lift
<b>PEDAIS</b>	Anti-slip Platform
TRANSMISSÃO	
<b>MANETES</b>	Shimano Cues 9-speed
<b>DESVIADOR TRASEIRO</b>	Shimano Cues 9-speed
<b>TRAVÕES</b>	Tektro HD-M281, hydraulic disc, 180mm [F] 160mm [R]
<b>MANÍPULOS DOS TRAVÕES</b>	Tektro HD-M281
<b>CASSETTE</b>	Shimano Cues 11-36T, 9-speed
<b>CORRENTE</b>	KMC E9 Sport NP/BK, e-bike optimized
<b>CONJUNTO PEDALEIRO</b>	Aluminum 38T

RODAS	
<b>AROS</b>	Liv GX03V 700c aluminium
<b>CUBOS</b>	Shimano center-lock 15x100mm [F], Shimano center-lock OLD 135mm [R]
<b>RAIOS</b>	Stainless steel
<b>PNEUS</b>	Maxxis MetroPass 28x2.2
ACESSÓRIOS	
<b>LUZES</b>	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
<b>CADEADO</b>	ABUS Xplus battery lock
<b>PORTA-BICICLETAS</b>	MIK System rack. Child seat, bag & basket compatible

Preço: 2 649,00 €

## GEOMETRIA

QUADRO	XS	S	M
Comprimento do tubo do assento (mm)	380	430	460
Ângulo do tubo do assento	74,0°	73,5°	73,0°
Comprimento do tubo superior (mm)	565	580	600
Comprimento do tubo principal (mm)	180	180	200
Ângulo do tubo principal	69,5°	69,5°	69,5°
Garfo ancinho (mm)	46	46	46
Trilha (mm)	94,5	94,5	94,5
distância entre eixos (mm)	1116	1137	1152
Comprimento Chain Stay (mm)	482	482	482
Suporte inferior (mm)	60	60	60
Pilha (mm)	662	662	681
Alcaçar (mm)	366	384	392
Altura do standover (mm)	427	428	431
Largura do guidão (mm)	660	660	660
Comprimento da haste (mm)	80	80	100
Comprimento da Manivela (mm)	165	165	170
Tamanho da roda	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.