

ALLURE E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
SENSOR	RideControl Ergo 2, RideControl GO integrated in D/T
DISPLAY	RideDash Evo
BATTERY	EnergyPak Smart Compact 500Wh
CADRU	
MARIMI	XS, S, M, L
CULORI	Grayish Blue, Desert Sage
CADRU	ALUXX Aluminum, Overdrive 1½ - 1½" head tube, integrated KS18 kickstand mount
FURCA	SR Suntour NEX E25, 50mm
SOC	-
COMPONENTE	
GHIDON	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Liv Comfort Ergo Microtech Plus
PIPA	Giant Contour, EVO display integrated, adjustable
TIJA SA	Suspension 2-bolt micro-adjustable, 30.9x300mm [S, M, L] Forged aluminum 30.9x250mm [XS]
SA	Selle Royal Lift
PEDALE	Aluminum Platform
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Nexus 7-speed RevoShift
SCHIMBATOR FATA	-
SCHIMBATOR SPATE	-
FRANE	Tektro HD-M275, hydraulic disc, 160mm [F/R]
MANETE FRANA	Tektro HD-M276
PINIOANE	18T
LANT	KMX Z1e HX, e-bike optimized
ANGRENAJ	Aluminum, 38T
BOTTOM BRACKET	N/A

ROTI	
JANTE	Liv GX03V, 700c aluminium
BUTUCI	Shimano HB-MT200 9mm QR Disc [F], Shimano Nexus 7 Disc brake [R]
SPITE	Stainless steel
ANVELOPE	Maxxis Metro Pass 622x50, 60tpi, Wire Bead, Reflective, ECE-R75
EXTRAS	-
ACCESSORIES	
LIGHTING	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
LOCK	-
CARRIER	MIK HD rack. system bag & basket compatible

GEOMETRIE

CADRU	XS	S	M	L
Seat Tube Length (mm)	380	450	500	550
Seat Tube Angle	74,0°	73,5°	73,0°	72,5°
Top Tube Length (mm)	570	580	595	610
Head Tube Length (mm)	180	180	200	200
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9
Wheelbase (mm)	1127	1131	1141	1150
Chain Stay Length (mm)	480	480	480	480
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	646	646	665	665
Reach (mm)	385	389	392	400
Handlebar Width (mm)	630	630	670	670
Stem Length (mm)	90	90	90	90
Crank Length (mm)	165	165	170	170
Wheel Size	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.