



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Core, 50Nm, Powered by YamahaCoaster Version
TIPALO	RideControl Ergo 2, RideControl GO integrated in D/T
PRIKAZOVALNIK	RideDash Evo
BATERIJA	EnergyPak Smart Compact 500Wh
OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Grayish Blue
OKVIR	ALUXX Aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
VILICE	SR Suntour NEX E25, 50mm
AMORTIZER	-
KOMPONENTE	
KRMILLO	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
GRIPS	Liv Comfort Ergo Microtech Plus
OPORA KRMILA	Giant Contour, EVO display integrated, adjustable
OPORA SEDEŽA	Suspension 2-bolt micro-adjustable, 30.9x300mm [S, M, L] Forged aluminum 30.9x250mm [XS]
SEDEŽ	Selle Royal Lift
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Nexus 8-speed RevoShift
PREDNJI MENJALNIK	-
ZADNJI MENJALNIK	-
ZAVORE	Tektro HD-M275, hydraulic disc, 160mm [F/R]
ZAVORNE ROČICE	Tektro HD-M276
VERIŽNIK	18T
VERIGA	KMX Z1e HX, e-bike optimized
GONILKE Z VERIŽNIKI	Aluminum, 38T
BOTTOM BRACKET	N/A

OBROČNIKI	
OBROČI	Liv GX03V, 700c aluminium
PESTA	Shimano HB-MT400 100x15mm thru-axle Disc [F], Shimano Nexus 8 Coaster / Disc brake [R]
NAPERE	Stainless steel
PLAŠČI	Maxxis Metro Pass 622x50, 60tpi, Wire Bead, Reflective, ECE-R75
DODATKI	-
DODATNA OPREMA	
SVETILA	Recon E HL50 StZVO [F] Axa BlueLine Steady E6 [R]
KLJUČAVNICA	-
PRTLJAŽNIK	MIK HD rack. system bag & basket compatible

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	380	450	500	550
Kot sedežne cevi	74,0°	73,5°	73,0°	72,5°
Top Tube Length (mm)	570	580	595	610
Višina glave okvirja (mm)	180	180	200	200
Krmilni kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	86,9	86,9	86,9	86,9
Medosna razdalja (mm)	1127	1131	1141	1150
Dolžina cevi ob verigi (mm)	480	480	480	480
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	646	646	665	665
Doseg (mm)	385	389	392	400
Širina krmila (mm)	630	630	670	670
Dolžina opore krmila (mm)	90	90	90	90
Dolžina gonilke (mm)	165	165	170	170
Velikost obročnikov	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.