



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Sport2, 75Nm, powered by Yamaha
TIPALO	RideControl Dash
PRIKAZOVALNIK	RideControl Dash, full color lcd screen
BATERIJA	EnergyPak Smart 625, EnergyPak Plus 250 range extender compatible (exclude XS size)
OKVIR	
VELIKOSTI	XS, S, M, L
OKVIR	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
VILICE	SR Suntour XCM34, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Connect Riser 31.8x620mm (XS/S), 690mm(M/L)
GRIPS	Liv Contact Ergo Max Plus
OPORA KRMILA	Giant Contact (XS/S/M: 80mm, L:100mm)
OPORA SEDEŽA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SEDEŽ	Liv Sport Comfort
PEDALA	Aluminum Platform
POGON	
PRESTAVNE ROČICE	Shimano Altus
PREDNJI MENJALNIK	n/a
ZADNJI MENJALNIK	Shimano Alivio, 9-speed
ZAVORE	Tektro HD-M276, hydraulic disc, 180mm
ZAVORNE ROČICE	Tektro HD-M276
VERIŽNIK	Shimano CS-HG200, 11-36T, 9-speed
VERIGA	KMC e.9 Sport, e-bike optimized
GONILKE Z VERIŽNIKI	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	eX25, Tubeless Ready, 622x25 Aluminium
PESTA	Giant eTracker, [F] 110x15 [R] 1142x12
NAPERE	Stainless steel
PLAŠČI	Crosscut Gravel 2, 700x57, Wire Bead, Tubeless Ready
DODATNA OPREMA	
SVETILA	Recon E HL50 StVZO [F]JAXA NYX 6-12V E-bike tail light [R]
KLJUČAVNICA	ABUS Xplus battery lock
PRTLJAŽNIK	MIK rack. System bag & basket compatible

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	380	410	435	490
Kot sedežne cevi	75,0°	74,5°	73,5°	73,0°
Top Tube Length (mm)	575	585	605	620
Višina glave okvirja (mm)	135	145	160	175
Krmilni kot	69,0°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	51	51	51	51
Trail (mm)	88	84	84	84
Medosna razdalja (mm)	1149	1148	1157	1166
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	660	672	686	700
Doseg (mm)	398	398	401	406
Višina zgornje cevi (mm)	676	684	663	676
Širina krmila (mm)	650	650	690	690
Dolžina opore krmila (mm)	80	80	100	100
Dolžina gonilke (mm)	165	165	170	170
Velikost obročnikov	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.