



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport, 70Nm, powered by Yamaha
CONTROLLER	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERY	EnergyPak 500
FRAME	
SIZES	XS, S, M, L
FRAME	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KSA18 kickstand mount
FORK	SR Suntour NEX DS 63mm travel
SHOCK	n/a
COMPONENTS	
HANDLEBAR	Giant Connect Riser 31.8x620mm (XS/S), 690mm(M/L)
GRIPS	Liv Contact Ergo Max Plus
STEM	Giant Contour TDS 816-8FOV (XS/S/M:80mm L 100mm)
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Sport Comfort
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano Altus
FRONT DERAILEUR	n/a
REAR DERAILEUR	Shimano Alivio, 9-speed
BRAKES	Tektro HD-M276, hydraulic disc, 180mm [F], 160mm [R]
BRAKE LEVERS	Tektro HD-M276
CASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
CHAIN	KMC e.9 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 42T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Giant eX 2, Tubeless Ready, 622x21 aluminium
HUBS	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
SPOKES	Stainless steel
TIRES	Giant Crosscut Gravel 2, 700x50c, Tubeless Ready
ACCESSORIES	
LIGHTING	Axa BlueLine 30Lux Steady E6 [F] Axa BlueLine Steady E6 [R]
CARRIER	MIK rack. System bag & basket compatible

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	385	435	485	535
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°
Top Tube Length (mm)	550	570	590	610
Head Tube Length (mm)	125	135	145	155
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	89	89	89	89
Wheelbase (mm)	1100	1115	1130	1145
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	616	625	635	644
Reach (mm)	379	391	402	413
Stand Over Height (mm)	613,1	596,2	584,3	554,2
Handlebar Width (mm)	690	690	730	730
Stem Length (mm)	40	50	60	70
Crank Length (mm)	165	170	170	172,5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.