AMITI E+ 45



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSORES	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, C (10W)
DISPLAY	Giant RideControl Dash high-angle visibility, full color LCD display
BATERÍA	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exclude STA frame)
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	M, L,
COLORES	Blue / Black
CUADRO	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
TIJERA	SR Suntour XCM34 LO, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Connect Riser 31.8x690mm
GRIPS	Liv Contact Ergo Max Plus
POTENCIA	Giant Contact (M: 80mm L/XL/XXL 100mm)
POSTE DE ASIENTO	Giant Contact
ASIENTO	Liv Sport Comfort
PEDALES	Aluminium Platform
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore LinkGlide
DESVIADOR	N/A
CAMBIO TRASERO	Shimano Cues Linkglide, 9-speed
FRENOS	Tektro HD-M275, hydraulic disc,180mm
PALANCAS DE FRENOS	Tektro HD-M275
CASSETTE	Shimano LinkGlide, CS-LG300-9, 11-41T, 9-speed
CADENA	KMC E9 Sport NP/BK, e-bike optimized
MULTIPLICACIÓN	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring
EJE DE CENTRO	N/A

RUEDAS	
RUEDAS	Giant eX25, Tubeless Ready, 622x25 Aluminium
MAZAS	Giant eTracker, [F] 110x15 [R] 148x12
RAYOS	Stainless steel, e-bike optimized
NEUMÁTICOS	Crosscut Gravel 2, 700x57c, Wire Bead, Tubeless Ready
EXTRAS	KSA40 direct mount kickstand MIK rack.
LIMITS	
COMPATIBILITY	System bag & basket compatible
ACCESORIOS	
LUCES	Recon E HL50 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
CANDADOS	ABUS Xplus battery lock

Precio: $66,900.00

GEOMETRÍA

CUADRO	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	385	435	485
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°
Longitud del Tubo Superior (mm)	550	570	590
Longitud del Telescopio (mm)	125	135	145
Ángulo del Telescopio	69.5°	69.5°	69.5°
Rake (mm)	44	44	44
Trail (mm)	89	89	89
Distancia entre Ejes (mm)	1100	1115	1130
Longitud de Vaina Inferior (mm)	470	470	470
Caída del Eje de Centro (mm)	60	60	60
Stack (mm)	616	625	635
Reach (mm)	379	391	402
Altura del Tubo Superior al Suelo (mm)	613.1	596.2	584.3
Ancho del Manubrio (mm)	690	690	730
Longitud de la Potencia (mm)	40	50	60
Longitud de la Biela (mm)	165	170	170
Tamaño de las Ruedas	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.