



## СПЕЦИФИКАЦИИ

| РАМКА                  |  |
|------------------------|--|
| РАЗМЕР                 | XXS, XS, S, M, L   |
| ЦВЯТ                   | Interstellar/Chrome  |
| РАМКА                  | Advanced-grade composite, 12x142mm thru-axle, disc                                       |
| ВИЛКА                  | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc     |
| ЗАДЕН АМОРТИСЬОР       | N/A  |
| КОМПОНЕНТИ             |  |
| КОРМИЛО                | Liv Contact SL D-Fuse, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm        |
| ГРИПОВЕ                | Liv Stratus Elite 2.0  |
| ЛАПА                   | Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm                   |
| КОЛЧЕ ЗА СЕДАЛКА       | Giant D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| СЕДАЛКА                | Liv Approach   |
| ПЕДАЛИ                 | platform pedal [GCS,GTS] N/A [all other GSC]   |
| DRIVETRAIN             |  |
| КОМАНДИ                | Shimano 105 Di2  |
| ПРЕДЕН ДЕРАЙЛЪОР       | Shimano 105 Di2  |
| ЗАДЕН ДЕРАЙЛЪОР        | Shimano 105 Di2  |
| СПИРАЧКИ               | Shimano 105 Di2 hydraulic, Shimano SM RT70 rotors [F]160mm, [R]160mm                     |
| РЪКОХВАТКИ ЗА СПИРАЧКИ | Shimano 105 Di2  |
| КАСЕТА                 | Shimano 105, 12-speed, 11x36   |
| ВЕРИГА                 | KMC X12  |
| КУРБЕЛ                 | Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm                 |
| СРЕДНА КАСЕТА          | Shimano, press fit   |

| КАПЛИ              |   |
|--------------------|---|
| ШИНИ               | Giant SLR 2 36 WheelSystem, [F] 36mm, [R] 36mm  |
| ГЛАВИНИ            | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t pawl driver, CenterLock, 12mm thru-axle |
| СПИЦИ              | Sapim Sprint  |
| ГУМИ               | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding  |
| ЕКСТРИ             | two bottle cage, fender mount, tubeless prepared, 40mm max tire size  |
| ЛИМИТИ             |   |
| MAX TIRE CLEARANCE | 40mm  |

## ГЕОМЕТРИЯ

| РАМКА                    | XXS   | XS    | S     | M     | L     |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 385   | 405   | 435   | 465   | 495   |
| Seat Tube Angle          | 75,0° | 74,5° | 74,5° | 74,0° | 74,0° |
| Top Tube Length (mm)     | 500   | 520   | 525   | 535   | 555   |
| Head Tube Length (mm)    | 110   | 125   | 145   | 165   | 185   |
| Head Tube Angle          | 69,8° | 71,0° | 71,0° | 71,0° | 72,0° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 76    | 68    | 68    | 68    | 61    |
| Wheelbase (mm)           | 989   | 995   | 1002  | 1007  | 1013  |
| Chain Stay Length (mm)   | 420   | 420   | 420   | 420   | 420   |
| Bottom Bracket Drop (mm) | 75    | 75    | 73    | 73    | 73    |
| Stack (mm)               | 510   | 528   | 547   | 566   | 589   |
| StackToHandlebar (mm)    | 588   | 606   | 626   | 647   | 668   |
| Обсер (mm)               | 363   | 373   | 373   | 373   | 381   |
| ReachToHandlebar (mm)    | 408   | 420   | 429   | 439   | 449   |
| Stand Over Height (mm)   | 683   | 712   | 737   | 762   | 789   |
| Ширина на Кормило (mm)   | 380   | 380   | 400   | 400   | 420   |
| Дължина на Лапа (mm)     | 70    | 70    | 80    | 90    | 90    |
| Дължина на Курбел (mm)   | 165   | 165   | 170   | 170   | 172,5 |
| Размер на Каплите        | 700C  | 700C  | 700C  | 700C  | 700C  |

All specifications listed are subject to change without notice.