

AVAIL ADVANCED 0



TEKNISET TIEDOT

| RUNKO | |
|----------------|---|
| KOOT | XXS, XS, S, M, L |
| VÄRIT | Camel Silk/Chrome |
| RUNKO | Advanced-grade composite, 12x142mm thru-axle, disc |
| HAARUKKA | Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| KOMPONENTIT | |
| OHJAUSTANKO | Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm |
| GRIPIT | Liv Stratus Elite 2.0 |
| OHJAINKANNATIN | Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm |
| SATULATOLPPA | Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| SATULA | Liv Approach |
| VOIMANSIIRTO | |
| VAIHDEVIPU | Shimano 105 Di2 |
| ETUVAIHTAJA | Shimano 105 Di2 |
| TAKAVAIHTAJA | Shimano 105 Di2 |
| JARRUT | Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors, [F]160mm, [R]160mm |
| JARRUKAHVAT | Shimano 105 Di2 |
| RATASPAKKA | Shimano 105, 12-speed, 11x36 |
| KETJUT | KMC X12 |
| KAMPISARJA | Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm |
| KESKIÖ | Shimano, press fit |

| RENKAAT | |
|----------------|---|
| VANTEET | Giant SLR 2 40 WheelSystem, [F] 40mm, [R] 40mm |
| NAVAT | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T pawl driver, CenterLock, 12mm thru-axle |
| PINNAT | Sapim Sprint |
| RENKAAT | Giant Gavia Fondo 0, tubeless, 700x32c, folding |
| LISÄTIEDOT | fender mount, tubeless prepared, 40mm max tire size |
| RAJOITTEET | |
| MAX RENGASVARA | 40mm |

Suositusuhinta: 4 299,00 €

GEOMETRIA

| RUNKO | XS | S | M | L |
|------------------------------------|-------|-------|-------|-------|
| Satulaputken pituus (mm) | 405 | 435 | 465 | 495 |
| Satulaputken kulma | 74,5° | 74,5° | 74,0° | 74,0° |
| Vaakaputken pituus (mm) | 520 | 525 | 535 | 550 |
| Emäputken pituus (mm) | 125 | 145 | 165 | 185 |
| Emäputken kulma | 71,0° | 71,0° | 71,0° | 72,0° |
| Haarukan offset (mm) | 50 | 50 | 50 | 50 |
| Trail-mitta (mm) | 68,3 | 68,3 | 68,3 | 61,8 |
| Akseliväli (mm) | 995 | 1002 | 1007 | 1013 |
| Takahaarukan alaputken pituus (mm) | 420 | 420 | 420 | 420 |
| Keskiön pudotus (mm) | 75 | 75 | 75 | 75 |
| Stack-mitta (mm) | 528 | 547 | 566 | 589 |
| Reach-mitta (mm) | 373 | 373 | 373 | 381 |
| Standover-mitta (mm) | 712 | 737 | 762 | 789 |
| Ohjaustangon leveys (mm) | 380 | 400 | 400 | 420 |
| Ohjainkannattimen pituus (mm) | 70 | 80 | 90 | 90 |
| Kammen pituus (mm) | 165 | 165 | 170 | 172,5 |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.