

AVAIL ADVANCED 0



SPECS

RAM	
STORLEKAR	XXS, XS, S, M, L
FÄRGER	Camel Silk/Chrome
RAM	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GREPPAR	Liv Stratus Elite 2.0
STAM	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Approach
DRIVLINJA	
VÄXLAR	Shimano 105 Di2
FRAMVÄXEL	Shimano 105 Di2
BAKVÄXEL	Shimano 105 Di2
BROMSAR	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors, [F]160mm, [R]160mm
BROMSSPAKAR	Shimano 105 Di2
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12
VEVPARTI	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant SLR 2 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T pawl driver, CenterLock, 12mm thru-axle
EKRAR	Sapim Sprint
DÄCK	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAFUNKTIONER	fender mount, tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 47 990,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	405	435	465	495
Vinkel sadelrör	74,5°	74,5°	74,0°	74,0°
Topprörets längd (mm)	520	525	535	550
Styrhuvud Längd (mm)	125	145	165	185
Vinkel styrhuvud	71,0°	71,0°	71,0°	72,0°
Gaffelvinkel (mm)	50	50	50	50
Spår (mm)	68,3	68,3	68,3	61,8
Hjulbas (mm)	995	1002	1007	1013
Kedjestagslängd (mm)	420	420	420	420
Nedre fäste Drop (mm)	75	75	75	75
Stack (mm)	528	547	566	589
Reach (mm)	373	373	373	381
Stå över höjden (mm)	712	737	762	789
Styrets bredd (mm)	380	400	400	420
Stamlängd (mm)	70	80	90	90
Vevlängd (mm)	165	165	170	172,5

All specifications listed are subject to change without notice.