

AVAIL ADVANCED 1



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Iron Rouge/Carbon/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GREB / STYRBÅND	Liv Stratus Elite 2.0
FREMPIND	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SADELPIND	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Approach
GEARGRUPPE	
SKIFTEGREB	Shimano 105 Di2
FORSKIFTER	Shimano 105 Di2
BAGSKIFTER	Shimano 105 Di2
BREMSE	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm
BREMSEGREB	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x36
KÆDE	KMC X12
KRANKSÆT	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant P-R1 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EGER	Sapim
DÆK	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EKSTRA	fender mount, tubeless prepared, 40mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	40mm

Pris: 28.699,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	405	435	465	495
Sadelrørvinkel	74,5°	74,5°	74,0°	74,0°
Overrørslængde (mm)	520	525	535	550
Kronrørslængde (mm)	125	145	165	185
Kronrørvinkel	71,0°	71,0°	71,0°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Sti (mm)	68,3	68,3	68,3	61,8
Akselafstand (mm)	995	1002	1007	1013
Kædestagslængde (mm)	420	420	420	420
Krankboks drop (mm)	75	75	75	75
Stack (mm)	528	547	566	589
Stack til styr (mm)	606	626	647	668
Reach (mm)	373	373	373	381
Reach til styr (mm)	420	429	439	449
Skridthøjde (mm)	712	737	762	789
Styrbredde (mm)	380	400	400	420
Frempindslængde (mm)	70	80	90	90
Pedalarmslængde (mm)	165	165	170	172,5

Alle de anførte specifikationer kan ændres uden varsel.