

AVAIL ADVANCED 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
FRAME	Advanced-Grade Composite, 12x142mm thru-axle
FORK	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8, Reach: 68mm, Drop: 120mm XXS: Down: 410 / Top: 380, XS: Down: 410 / Top: 380, S: Down: 430 / Top: 400, M: Down: 430 / Top: 400, L: Down: 450 / Top: 420
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact Aerolight, -10° XXS: 70, XS: 70, S: 80, M: 90, L: 90
SEATPOST	Giant D-Fuse Composite Offset 14mm
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2 HRD
FRONT DERAILLEUR	Shimano 105 Di2
REAR DERAILLEUR	Shimano 105 Di2
BRAKES	Shimano 105 Di2 Hydraulic, Shimano SM-RT64, [F]160 [R]160
BRAKE LEVERS	Shimano 105 Di2 Hydraulic
CASSETTE	Shimano 105, 11x36, 12 speed
CHAIN	KMC X12
CRANKSET	Shimano 105 FC-R7100, 50/34, 12-speed XXS: 160, XS: 165, S: 165, M: 170, L: 172.5
BOTTOM BRACKET	Shimano, PressFit

WHEELS	
RIMS	Giant P-R1 Disc 12mm Thru-Axle
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 0 Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
EXTRAS	tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	700x40mm

Suggested Retail Price (CDN): \$4,499.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	385	405	435	465	495
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°
Top Tube Length (mm)	500	520	525	535	550
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	69.8°	71.0°	71.0°	71.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76.2	68.3	68.3	68.3	61.8
Wheelbase (mm)	989	995	1002	1007	1013
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	75	75
Stack (mm)	510	528	547	566	589
StackToHandlebar (mm)	588	606	626	647	668
Reach (mm)	363	373	373	373	381
ReachToHandlebar (mm)	408	420	429	439	449
Stand Over Height (mm)	683	712	737	762	789
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	160	165	165	170	172.5

All prices and specifications are subject to change without notice.