

AVAIL ADVANCED 1



SPECIFIKACIJE

| OKVIR | |
|---------------------|--|
| VELIČINE | XXS, XS, S, M, L |
| BOJE | Mechanic Rose |
| OKVIR | Advanced-grade composite, 12x142mm thru-axle, disc |
| VILICA | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| AMORTIZER | N/A |
| KOMPONENTE | |
| VOLAN | Liv Contact SL D-Fuse, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm |
| GRIPS | Liv Stratus Elite 2.0 |
| LULA VOLANA | Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm |
| CIJEV SJEDALA | Giant D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| SJEDALO | Liv Approach |
| PEDALE | platform pedal [GCS,GTS] N/A [all other GSC] |
| POGON | |
| RUČICE MJENJAČA | Shimano 105 Di2 |
| PREDNJI MJENJAČ | Shimano 105 Di2 |
| STRAŽNJI MJENJAČ | Shimano 105 Di2 |
| KOČNICE | Shimano 105 Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]160mm |
| RUČICE KOČNICA | Shimano 105 Di2 |
| KAZETA | Shimano 105, 12-speed, 11x36 |
| LANAC | KMC X12 |
| POGON | Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm |
| OSOVINA POGONA (BB) | Shimano, press fit |

| KOTAČI | |
|--------------------|--|
| OBRUČI | Giant P-R2 Disc wheelset, alloy |
| NABE | Giant alloy, 12mm thru-axle |
| ŽBICE | Sapim |
| GUME | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding |
| DODACI | two bottle cage, fender mount, tubeless prepared, 40mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 40mm |

GEOMETRIJA

| OKVIR | XXS | XS | S | M | L |
|--|-------|-------|-------|-------|-------|
| Dužina cijevi sjedala (mm) | 385 | 405 | 435 | 465 | 495 |
| Kut cijevi sjedala | 75,0° | 74,5° | 74,5° | 74,0° | 74,0° |
| Dužina gornje cijevi (mm) | 500 | 520 | 525 | 535 | 555 |
| Dužina prednje cijevi (mm) | 110 | 125 | 145 | 165 | 185 |
| Kut vilice | 69,8° | 71,0° | 71,0° | 71,0° | 72,0° |
| Zakrivljenost vilice (offset) (mm) | 50 | 50 | 50 | 50 | 50 |
| Staza (mm) | 76 | 68 | 68 | 68 | 61 |
| Međuosovinski razmak kotača (mm) | 989 | 995 | 1002 | 1007 | 1013 |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm) | 420 | 420 | 420 | 420 | 420 |
| Položaj osovine pogona (mm) | 75 | 75 | 73 | 73 | 73 |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm) | 510 | 528 | 547 | 566 | 589 |
| StackToHandlebar (mm) | 588 | 606 | 626 | 647 | 668 |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 363 | 373 | 373 | 373 | 381 |
| ReachToHandlebar (mm) | 408 | 420 | 429 | 439 | 449 |
| Prekoračna visina (mm) | 683 | 712 | 737 | 762 | 789 |
| Širina volana (mm) | 380 | 380 | 400 | 400 | 420 |
| Dužina lule volana (mm) | 70 | 70 | 80 | 90 | 90 |
| Dužina poluge pedale (mm) | 165 | 165 | 170 | 170 | 172,5 |
| Veličina kotača | 700C | 700C | 700C | 700C | 700C |

Sve navedene specifikacije podložne su promjeni bez prethodne najave.