

AVAIL ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Iron Rouge/Carbon/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
CIJEV SJEDALA	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SJEDALO	Liv Approach
POGON	
RUČICE MJENJAČA	Shimano 105 Di2
PREDNJI MJENJAČ	Shimano 105 Di2
STRAŽNJI MJENJAČ	Shimano 105 Di2
KOČNICE	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm
RUČICE KOČNICA	Shimano 105 Di2
KAZETA	Shimano 105, 12-speed, 11x36
LANAC	KMC X12
POGON	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant P-R1 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
ŽBICE	Sapim
GUME	Giant Gavia Fondo 0, tubeless, 700x32c, folding
DODACI	fender mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	385	405	435	465	495
Kut cijevi sjedala	75,0°	74,5°	74,5°	74,0°	74,0°
Dužina gornje cijevi (mm)	500	520	525	535	550
Dužina prednje cijevi (mm)	110	125	145	165	185
Kut vilice	69,8°	71,0°	71,0°	71,0°	72,0°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50
Staza (mm)	76,2	68,3	68,3	68,3	61,8
Međusovinski razmak kotača (mm)	989	995	1002	1007	1013
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420
Položaj osovine pogona (mm)	75	75	75	75	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	510	528	547	566	589
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	363	373	373	373	381
Prekoračna visina (mm)	683	712	737	762	789
Širina volana (mm)	380	380	400	400	420
Dužina lule volana (mm)	70	70	80	90	90
Dužina poluge pedale (mm)	160	165	165	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.